

# HIGH DEFINITION SMART CAMERA

## VP-DC400P2PCN IR NIGHT VISION WIFI PAN-TILT CAMERA



### FEATURES

720P HD video technology

Smart IR with intensity control for true & day night vision

Two way audio intercom technology

Alarm push technology

Network auto-adaptive technology

Automatically device ID No. searching while shaking

Plug and play technology



1/3"  
Progressive  
Scan Sensor



**P2P**



**SD Card**



**0 Lux**



VP-DC400P2PCN

VideoCompression	Operation System	H.264 Baseline profile
Video	Image Sensor	1/3" progressive scan Sensor
	Core Chipset	Hi3518E Chipset
	Resolution	720P HD images, resolution up to 1280x720,1.0MP
	Resolution Variable	720P(1280x 720),VGA(640 x 360), QVGA(320 x 180)
	Frame Rate	1~30fps
	Min. Illumination	Color: 0.01 Lux; W/B: 0 Lux with IR LED ON
	IR Distance	Dual IR cut filter with auto switch,2pcs high-power smart IR LEDs, night vision up to 10 meters range
	S/N Ratio	≥ 62 dB
	CMOS Features	Support AWB, AGC,BLC
	Lens/Visual Angel	3.6mm mega-pixel lens@F1.4 /56.14°
System Feature	Security	Account, password two level user authentication
	Adaptive dynamic IP domain name system(Free)	No need domain name, support dynamic IP, no application of "peanutshells", completely solve the problem of frequently dropped calls, connection with high speed
	Mobile phone monitor	Support megapixel HD mobile phone monitor, dedicated IPHONE software, Android software(Software version required IOS4.3,Android 2.3 and above)
	On-board storage	Support external 128GB TF card,24 hours recording, More than 32GB need to be formatted as FAT32
	Plug and Play	Adopting advanced Cloud-link P2P (Plug and play) technology, network penetration up to 99%, applicable to all kinds of complex networks, installation takes only three steps: 1. Connecting power supply and network, 2. Installing mobile phone software; 3. Viewing CCTV images.
	Server Clusters	P2P intelligent clusters of servers throughout the world, protect the pan-tilt home IP camera works stable and efficient
Audio	Audio compression	G.711A
	Audio Input	1CH
	Audio Output	Built-in speaker(8Ω1W)
PTZ Control	Pan & Tilt	Horizontal 355°,vertical 120°
Video Management	Recording Mode	Manual recording, timing recording and alarm recording
	Video Storage	TF Card (support Max.128G)
Network	Ethernet	10Base -T, /100Base-TX, RJ45 Connector
	Protocols	TCP/IP,HTTP,TCP,UDP,SMTP, DHCP,DNS,DDNS,NTP,UPnP,P2P
	Wireless	WiFi 802.11b/g/n wireless network
Alarm	Alarm Input	1CH
	Alarm out	1CH
	Motion Detection	Supported
	Alarm Detection	Max. 64ch wireless alarm sensor, support one key defense setting and delete
	Alarm Action 1	Speaker alarm and call 5 different mobile phones
	Alarm Action 2	Capture photos and send by E-mail

## TECHNICAL SPECIFICATIONS

# VP-DC400P2PCN

System Requirement	System Configuration	Software version IOS, Android 2.3 and above
General	Enclosure	Indoor Pan-tilt Enclosure
	Power Supply	DC5V 2A
	Working Temperature	-10~50 °C
	Working Humidity	95% RH
	Dimensions	104x102x117mm (L x W x H)
	Weight	300g
Certification	Certification	CE, FCC, RoHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: [sales@vantagesecurity.com](mailto:sales@vantagesecurity.com)

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

