

# HIGH PERFORMANCE H.265 NETWORK VIDEO RECORDER

## VV-NV3532-8ST1 32 CHANNEL NVR



### FEATURES

ONVIF Supported

Up to 5 Megapixels Resolution Display and Recording

H.265 video compression technology with real time encoding


Full function CMS (Central monitoring software) supported

Two way audio supported

Dual Gigabit (10/100/1000) network port

Dual streaming technology to encode recording stream and network stream separately

Supports remote monitoring on Mobile Client (Android, IOS) and IE



## TECHNICAL SPECIFICATIONS

### VV-NV3532-8ST1

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	User interface	Support 16-bit true color graphical menu interface and mouse operation
Interface	IP Video Input	32-ch
	Two way Audio Input	1-ch, RCA (2.0 Vp-p, 1kΩ)
	VGA Video Output	1-ch, Resolution: 1920x1080P/60Hz,
	HDMI Video Output	2-ch, Resolution: 1920x1080P/60Hz, 4KX2K/60Hz
	Audio Output	1-ch, RCA (2.0 Vp-p, 1kΩ)
	Network	2 x Gigabit (10/100/1000) ethernet port (Rj45)
	USB	USB 3.0 x 1, x USB 2.0 x 2(one for mouse, another for USB backup device)
	Alarm Input/Output	16/4 CH
	E-sata Port	1
Resolution & Frame Rate	RS-485 Port	RS485 x 2, one for PTZ, another for Keyboard
	Recording Resolution	5MP/ 4Mp / 3MP / 1080P / 720P / 4CIF
	Frame Rate	Main stream: 25 fps (P) / 30 fps (N); Sub stream: 25 fps (P) / 30 fps (N)
	Playback Resolution	5MP/ 4Mp / 3MP / 1080P / 720P / 4CIF
Network & Remote Monitoring	Max playback capability	Max 4 ch playback
	DDNS	Supported; Dynamic and Static IP support
	CMS	Full function CMS (Central Monitoring Software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
Features	Bandwidth control	CBR (Manual) supported
	Security	Password protection, user management
	Playback Function	Play/Pause/Fast forward / backward/Digital zoom
	Search Mode	Time/Date, Alarm, Motion Detection & Exact Search (accurate to second)
Recording & Storage	Alarm Notifications	FTP, Email notification supported
	Recording Mode	Manual/Alarm/Motion Detection/Continuous
	Storage	8 SATA port up to 4TB each
General	Overwrite Mode	Supported
	Power Supply	ATX
	Power Consumption	<30W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	95% or less (non condensing)
	Chassis	Standalone 1U chassis
Certifications	Dimensions	430 x 450 x 89 mm
	Weight	≤4 Kg ( without hard disk)
	Certifications	CE,FCC,RoHS

\*Actual product and specifications may differ from the images appearing in the brochure and are subject to change without notice due to ongoing product development.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO 14001: 2004 CERTIFIED COMPANY)

