

ELECTRONIC SMART LOCKING SYSTEM

VP-DGLxxS-PLJ5 ELECTRONIC VANDAL PROOF STEEL PAD LOCK



FEATURES

- Combines the robustness of mechanized digital lock with the convenience of electronic operation for superior security
- Constructed from premium hardened steel providing exceptional strength and durability for a wide range of high security application
- Advanced control method using smart keys for easy and secure access with audit trails for seamless management
- Access audit logs for up to 60 locking events to enable monitoring and tracking of access records
- Anti-tamper, break proof, chemical resistant providing excellent resistance to physical attacks and electrostatic discharge
- Anti-pick capabilities with no key way for added security
- Provides extensive key management and control for up to 100 keys with blacklist key audit logs
- Built-in battery with an extended operational life of up to 10 years

VP-DGLxxS-PLJ5

Parameter	Specifications			
Lock Variant Model	VP-DGL60S-PLJ5	VP-DGL65S- PLJ5	VP-DGL70S -PLJ5	VP-DGL75S- PLJ5
Body Dimension	55mm x 60mm x 25mm	55mm x 65mm x 25mm	55mm x 70mm x 25mm	55mm x 75mm x 25mm
Shackle Dimension(h*w*d)	30.5mm(customized)* 24.5mmx12mm	30.5mm(customized)* 24.5mmx12mm	30.5mm(customized)* 24.5mmx12mm	30.5mm(customized)* 24.5mmx12mm
Operation Mode	Electro-Mechanical			
Operation Method	Smart digital biometric and non biometric keys			
Lock Body Material	Hardened-steel, with brushed finish surface treatment			
Lock Cylinder Material	SUS 304 grade stainless steel with ESD protection			
Access Audit Logs	60 locking event records			
Operation Life	More than 10 years			
Electronic Core Protection	Multiple protection from over-voltage, over-current and static electricity			
Physical Hardware Protection	Anti-tamper, drill resistant, torque break resistant, chemical resistant, anti-pick with no keyway security			
Blacklist Key Audit Logs	Up to 100 keys			
Power Source	Powered by biometric and non biometric smart keys			
Operating Environment	-45°C to 85°C			
Operating Humidity	<95% or less non condensing			
Ingress Protection	IP68			
Explosion Proof Rating	EX IIB IIC T4 GB			
Weight	598g	678g	755g	830g
Certification	CE, FCC, RoHS			

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary due to customized solutions & products being offered as per customer requirements.

VANTAGE INTEGRATED SECURITY SOLUTIONS

UK Head Office :

B3, Bredon House 321, Tettenhall
Road Tettenhall, Wolverhampton
West Midlands, WV6 0JZ United Kingdom
Email : sales@vantagesecurity.com

India Head Office : B-5, Sector 7,

Noida, (U.P.)- 201301, India
Email : sales@vantagesecurity.com

India Factory & Works :

B-11, Sector 7,
Noida, (U.P.)- 201301, India

ISO 9001 : 2015

ISO 14001 : 2015

ISO 27001 : 2013

CERTIFIED COMPANY

www.vantagesecurity.com