

SMART KIOSK INTERACTIVE SYSTEM

V-IK550P-V1

MULTI-PURPOSE KIOSK WITH EMBEDDED SYSTEM



FEATURES

Bright interactive display for sharp visuals with high-resolution 21 inch monitor ensures visibility in any lighting condition

Seamlessly navigate with multi-touch technology for an intuitive and responsive user experience

Equipped with a high-performance processor to ensure smooth and efficient operation for a variety of application scenarios

Built-in high-definition camera designed for clear and reliable video conferencing paired with high-quality audio components for an immersive communication experience

Reliable connectivity with built-Ethernet and optional Wi-Fi network capability

Ample storage capacity to manage with ease all necessary data, applications, and media

Water and dust resistant vandal-proof design to withstand rugged use, prevent tampering and damage

Thoughtfully engineered with rear access for easy maintenance, reducing downtime and ensuring continuous operation

V-IK550P-V1

Parameter	Specifications
Screen Resolution	1920x1080
Display Size	55cm (21.5")
Display Area	476 x 268 (mm)
Display Type	Wide Screen Backlit Color LED
Touch Screen Technology	Capacitive
Touch Signal	Supports bare finger/ thin gloves
Touch Response Time	≤ 5ms
Display Surface Finish	Anti glare toughened glass
Aspect Ratio	Wide 16:9
Contrast Ratio	10000:01
Pixel Pitch	0.248
Colour Brightness	> 16.8 Million
Brightness	500 cd/m ²
Angle of View	Horizontal 170°, Vertical 170°
Display Protection	Durable IP64 sealed monitor, sustain alcohol wipe/spray sanitization
Connectors & Interface	Power : DC 19V, Display: HDMI , USB, capacitive touch signal
Display Power Consumption	Max 100W
Central Processor	Quad Core Intel i5 2.5 Ghz 6th Gen
Operating System	Windows 10 Pro
RAM	8GB
EMMC	512 GB storage
Communication Interface	RJ45 TCP/IP LAN port, 2 x USB ports
Speaker, Keyboard, Mouse	Speaker, metal keybaord mouse with metal ball supported
Max. Power Consumption	115W
Power Consumption (Standby)	≤5W
Audio Video Camera	Full HD 1080p resolution VC camera
Field of View	78° diagonal FOV
Video Quality	Auto optimizable resolution supported- 1080p (Full HD) @30 fps, and 720p (HD) @ 30fps
Audio Quality	Built-in omni-directional microphone with up to 1 meter range for high clarity audio
Privacy Shutter	Supported
Brightness Control	Ambient adaptive light control supported
USB Communication	Supported
Floor Stand Kiosk	Provision for 21.5" touchscreen monitor, power distribution unit, internal chambers with rear access for monitor, CPU, UPS installation
Cabinet Construction	CRCA Sheet Metal 1.6mm, IP44
Cabinet Access	2 x lockable rear doors for monitor and CPU/UPS
Cabinet Color	Electrostatic polymer powder coating, exterior/interior with optional color
Cooling	Heat exhaust built In dual fans
Grouting	Supported concealed holes in base
Surface Protection	Resistant to most corrosives, not affected by surface contaminants like dust, grease, moisture, liquids, paan stains
Storage Temperature	-20° to 50° C
Operating Temperature	-30° to 70° C
Relative Humidity	95% or less Non-Condensing
Dimension	617mmx80mmx1250mm
Weight	90kg
Certifications	CE, FCC, ROHS

VANTAGE INTEGRATED SECURITY SOLUTIONS

UK Head Office :

B3, Bredon House 321, Tettenhall
Road Tettenhall, Wolverhampton
West Midlands, WV6 0JZ United Kingdom
Email : sales@vantagesecurity.com

India Head Office : B-5, Sector 7,

Noida, (U.P.)- 201301, India
Email : sales@vantagesecurity.com

India Factory & Works :

B-11, Sector 7,
Noida, (U.P.)- 201301, India

ISO 9001 : 2015

ISO 14001 : 2015

ISO 27001 : 2013

CERTIFIED COMPANY

www.vantagesecurity.com