

# ENTRANCE MANAGEMENT SYSTEM

## VV-VM5903EB-R1S4/L1S4 Ultra Fast Electronic Boom Barrier



### FEATURES

High Performance Boom Barrier with Electro-Mechanical Motor

100% duty cycle with >1 million operations

Opening time & Closing time 1.5 seconds


Arm Auto Reverse, Traffic Light can be integrated to further enhance safety

IP44 Ingress Protection Rating and Hand crank for Manual operations

Push button with up, down and stop functionality

Integration support with any RFID/Biometric Reader through NO input

Aluminium Telescopic Boom up to 3mtrs length supported



## TECHNICAL SPECIFICATIONS

### VV-VM5903EB-R1S4/L1S4

Parameter	Specifications
Drive	Torque Motor
Service Life	≥ 1 million
Rod Type	Straight boom
Rod Lift Time	1-5s
Rod Length	3m
Maximum Remote Control Distance	30m
Motor Power Consumption	100W
Frequency	60HZ/50HZ
Working Voltage	AC220/110V ±10%V
Operating Temp.	-40°to 85°
Barrier Dimension.	340x280x1030(mm
Gross Weight	55 kg
Certifications	CE, FCC, ROHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: [sales@vantagesecurity.com](mailto:sales@vantagesecurity.com)

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

