

PEOPLE ENTRANCE MANAGEMENT SYSTEM

V-PM4000-SGT3 P TYPE SWING GATE BARRIER



FEATURES

Selectable operating modes- single direction, bi-direction, always free or always locked

Heavy-duty design for 24 hours continue application

LED Direction indicators at each side

IP54 Ingress Protection rating

Automatic reset of barrier gate after each passage

Passage clearance up to 600mm

Integration support with any smart card, RFID/ Biometric Reader through NO input

Top quality AISI 304 grade SS construction



LED Direction Indicators



INGRESS PROTECTION RATING

IP54



100% Duty Cycle



Delay Time



Wired Terminal

TECHNICAL SPECIFICATIONS

V-PM4000-SGT3

Parameter	Specifications
Passage width	600mm (900mm Optional)
Throughput rate	10 to 20 p/m with access control and without access control
Drive	Electro machnical motor
Locking mechanism	Automatically
Fail safe & Fail lock	Fail safe & Fail lock variants in the event of removal of power supply
Power supply	100~240 V A
Operational voltage	24 V DC
Frequency	50~60 Hz
Humidity	95% non-condensing
Protection level	IP54
Working temperature	-10°C ~+55°C
Power consumption	35W
Dimension	200x200x980mm
Net weight	Approx. 35 kg
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

