

PEOPLE ENTRANCE MANAGEMENT SYSTEM

V-PM4300SC-SGT3

SLIDING GATE BARRIER WITH FIBER GLASS



FEATURES

Heavy duty stainless steel sliding gate barrier with fiber glass gates

Single and Bi-directional operations supported

LED Direction indicators at each side

Combination of infrared sensors used for smooth pedestrian access

Display use for statistics with voice & strobe light alerts

Double anti-clipping function, photocell anti-clipping and mechanical anti-clipping

IC cards, ID card, bar code or magnetic card used as automatic identification, access, attendance fees or function

Top quality AISI304 grade SS construction



LED Direction
Indicators

INGRESS
PROTECTION
RATING

IP44



100%
Duty Cycle



Delay Time



Wired
Terminal

TECHNICAL SPECIFICATIONS

V-PM4300SC-SGT3

Parameter	Specifications
Machine Core	Single
Passage Width	≤600mm
Sliding Glass Height	1200mm
Throughput Rate	35 p/m
Power Supply	100~240 V AC
Operational Voltage	24 V DC
Max Power Consumption	35W
Frequency	50~60 Hz
Protection Level	IP44
Working Temperature	-25°C~+70°C
Electro-Magnetic Drive	DC
Dimension	1400x300x980mm
Net Weight	95kg
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO9001 : 2008, ISO14001:2004 CERTIFIED COMPANY)

