

PEOPLE ENTRANCE MANAGEMENT SYSTEM

V-PM4500DC-SGT3 DOUBLE CORE SWING BARRIER GATE



FEATURES

Selectable operating modes- double direction, bi-direction, always free or always locked

Heavy duty stainless steel Swing Barrier with Fiber glass gates

LED Direction indicators at each side

IP54 Ingress Protection rating

Automatic reset of barrier gate after each passage

Adjustable time out delay

Double anti-clipping function, photocell anti-clipping and mechanical anti-clipping

Integration support with any RFID/Biometric Reader through NO input

Top quality AISI 304 grade SS construction



LED Direction Indicators

INGRESS PROTECTION RATING

IP54



100% Duty Cycle



Delay Time



Wired Terminal

TECHNICAL SPECIFICATIONS

V-PM4500DC-SGT3

Parameter	Specifications
Motor	Brushless servo motor
Passage width	600mm
Throughput rate	30 p/m
Flap Type	Transparent acrylic flap 10mm
Power supply	100~240 V AC
Operational voltage	24 VDC
Max power consumption	100W
Frequency	50~60 Hz
Protection level	IP54
Working temperature	-25°C~+70°C
Electro-magnetic drive	DC
Dimension	1500x150x980mm
Net weight	65 kg
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image & weights, measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

