



## **SPECIAL APPLICATION CAMERA**

# **VP-AC150-SCG3**

**Wireless Inspection Camera With Color LCD Monitor** 





### **FEATURES**

Inbuilt 2.4" Wireless TFT monitor with rechargeable battery

Allows for easy visual inspection of hard to reach areas.

Compact and handheld design for easy operations

High resolution camera

IP67 water proof enclosure







# VP-AC150-SCG3

Camera	Imaging Sensor	High Performance CMOS Sensor
	Effective Pixels	640 x 480 (PAL) 640 X 480 (NTSC)
	Horizontal Angle of View	45°
	Transmission Frequency	2468MHz
	Minimum illumination	0 Lux
	Modulation Type	Frequency Modulation
	Bandwidth	10MHz
	Power Supply	4 x AA Batteries
	Unobstructed Effective Range	Max.10m
	Enclosure	IP67 Waterproof Enclosure
	Tube Diameter	9mm
Receiver	TFT Screen Type	2.36" TFT
	Effective Pixels	480 x 240
	Video System	PAL / NTSC
	Transmission Frequency	2468MHz
	Exterior Supply Voltage	8V-24V
	Power Consumption	490mA
	Video Output	0.9-1.3 Vpp@75 ohm
	Receiving Sensitivity	85dBm
Genral	Dimensions (Receiver)	100 x 70 x 30 mm
	Approx, Weight (Receiver)	140g
	Operating Temperature (Receiver)	-10°C~55°C
	Operating Humidity (Receiver)	0~95%RH (non condensing)
	Dimensions (Camera)	186 x 145 x 41 mm
	Approx. Weight (Camera)	450g
Certifications	Certifications	CE, FCC, RoHS

<sup>\*</sup>Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com





(AN ISO 9001: 2008, ISO14001: 2004 CERTIFIED COMPANY)

