

FULL HIGH DEFINITION 2MP FIXED DOME CAMERA

VP-AC2M47D-M02F3P1K3
IR Night Vision FULL HD Camera



FEATURES

2 Megapixel Full HD Resolution

HD video output supported

High performance IR Cut mechanical filter for True Day & Night vision

3.8mm Lens

High performance smart IR LEDs with intensity control

IP66 Weather proof enclosure



1/2.7" Progressive
Scan CMOS Sensor



Smart IR



Auto White
Balance



3D DNR

TECHNICAL SPECIFICATIONS

VP-AC2M47D-M02F3P1K3

Camera	Image sensor	1/2.7" Progressive Scan CMOS Sensor
	Signal System	PAL/NTSC
	Effective Pixels	1930 (H) × 1088(V)
	Frequency	50 Hz (PAL) / 60 Hz (NTSC)
	Horizontal Resolution	2 Megapixel
	Minimum Illumination	Color : 0.01Lux @ F1.2, 0 Lux at IR on
	Signal to Noise	> 52 dB
	Shutter Time	1/25s ~ 1/100,000s
	Gain Control	Auto
	White Balance	Auto
	DNR	Inbuilt 3D DNR (Digital Noise Reduction) circuit
Lens	Lens Type	3.8mm Lens
	Lens Mount	M12
	Focus	Fixed
Day/Night Functionality	Day & Night	True Day & Night with ICR
	IR Cut	High performance Mechanical IR Cut Filter with auto switch
	IR Source	High performance smart IR LEDs with intensity control
	IR Range	Up to 20 Mtrs
Interface	HD Video Output	Supported
	Power Input	Standard DC Jack
Electrical	Power Requirement	DC 12V (± 10%)
	Power Consumption	Max 5 W with IR on
Environmental	Enclosure	IP 66 Weather proof enclosure
	Operating Temperature	-10°C to + 60°C
	Operating Humidity	90% or less (non-condensing)
Mechanical	Color	White
	Dimensions	120x120x93mm
	Weight	280g
Certification	Certification	UL, CE, FCC, RoHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

