

BIOMETRIC BASED ACCESS CONTROL SYSTEM

VP-CD4DP-2WZ1 FOUR DOOR TWO WAY BIOMETRIC CONTROLLER



FEATURES

Stores up to 3,000 fingerprint templates, 30,000 card users, and up to 100,000 events and transactions

Supports TCP/IP, RS-485 communication and Wiegand interface for RFID reader

Internal biometric identification supports fast and accurate matching with stored templates in database

On-board SD card for data backup for uninterrupted operation in case of power failure

Built in Anti-Passback, First-Card Opening, Multi-Card Opening, Duress Password Entry and Auxiliary Input/Output linkages

Auto-discovery tool allows setting and modification of network parameters directly and easily

TECHNICAL SPECIFICATIONS

VP-CD4DP-2WZ1

Parameter	Specifications
Number of doors controller	4 Door
Numbers of readers supported	12 (8 RS-485 Reader, 4 26-bit wiegand reader)
Types of readers supported	26-bit Wiegand and RS485 Reader
Number of Inputs	12 (4 Exit Device, 4 Door Status, 4 AUX)
Number of Outputs	8 (4-Form C Relay for Lock and 4-Form C Relay for Aux Output)
Card holders Capacity	30,000
Fingerprint Capacity	3,000
Log Events Capacity	100,000
Communication	TCP/IP and RS-485
CPU	32 bit 400MHz CPU
RAM	32M
Flash Memory	128M
Power	9.6V-14.4V DC
Operating Temperature	0-50 °C
Operating Humidity	20% to 80%
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

