

IP VIDEO DOOR PHONE SYSTEM

VP-CS70GS-IPV2 GUARD MANAGEMENT UNIT



FEATURES

Protocol: Standard TCP/IP

7inch capacitive touch screen with advanced GUI

Card management function for ID card registration

Supports SOS master reset for opening all apartment doors incase of emergency

Alarm management function

Supports IP CCTV cameras

Supports Intercom function

Communication with Management software for master programming



Camera
Interface



7" Color LCD
Display



Two way audio



ID Card



TCP/IP

TECHNICAL SPECIFICATIONS

VP-CS70GS-IPV2

Parameter	Specifications
Display	7" TFT LCD
Camera Pixels	0.3M
Display Resolution	800x480
Display Type	Capacitive touch screen
Touch Screen	Yes
Network	Ethernet (10/100Base-T) RJ-45
System	GVS Customized OS
Cabling Type	Cat-5
Memory	8M
Flash	16M
Power supply	DC12-24V
Rated Power	5W
Static Current	≤80mA
Working Current	≤200mA
Temperature	-10°C - +55°C
Humidity	20%-93%
Dimension (W/H/D)	305x210x31.8 mm
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

