

FULL HIGH DEFINITION 5MP IP BULLET CAMERA

VP-NC2615B-AF3IRL3 IR NIGHT VISION FIXED CAMERA



FEATURES

5 Megapixel Full HD resolution

1/2.7" Progressive Scan CMOS Sensor

Inbuilt Smart IR LEDs with intensity control

High performance IR Cut mechanical filter for True Day & Night vision


Inbuilt 3D DNR & BLC functions

Support Triple streams

Support P2P

Onvif supported

IP66 Weather proof outdoor enclosure



TECHNICAL SPECIFICATIONS

VP-NC2615B-AF3IRL3

| | | |
|--------------------------------|----------------------------------|--|
| Camera | Image sensor | 1/2.7" Progressive Scan CMOS Sensor |
| | Signal System | PAL/NTSC |
| | Effective Pixels | 2592(H) x 1944 (V) |
| | Minimum Illumination | Color : 0.01Lux @ F1.2, 0.015 lux @ F1.4, B&W: 0 Lux at IR on |
| | Electronic Shutter Speed | 1/25-1/10000Sec |
| | Gain Control | Auto |
| | White Balance | Auto |
| | Signal to Noise | > 52 dB |
| Lens | Lens Type | 3.6mm Fixed Lens |
| | Lens Mount | M12 |
| | Focus | Fixed |
| Day/Night Functionality | Day & Night | True Day & Night with ICR |
| | IR Cut | High performance Mechanical IR Cut Filter with auto switch |
| | IR Source | Inbuilt Smart IR LEDs with intensity control |
| | IR Range | Up to 25 Mtr. |
| Compression | Video compression | H.265/ H.264/ AVI /MJPEG |
| | H.265 codec profile | Main profile |
| | Video Bit Rate | 256 Kbps ~ 16 Mbps |
| Resolution and Frame Rate | Max. Resolution | 2592x1944 |
| | Main Stream | 2592x1944@15fp, 2560x1920@15fp,2560x*1440@30fp 1920x1080@30fps, 1280x720@30fps |
| | Sub / Third Stream | 720x480@15fps, 720x480@30fps,352x288@15fps,352x288@30fps |
| Operational Features | Privacy masking | Support up to 3 zones |
| | BLC & WDR | Supported |
| | DNR | Inbuilt 3D DNR (Digital Noise Reduction) circuit |
| | Codec streaming capability | Triple streaming |
| | Image settings | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK(Flicker Control), Video Tampering,Corridor Pattern |
| | Security | User Authentication |
| | Defog & Corridor Mode | Supported |
| | SD Card Slot | Supports Max 128GB (Optional) |
| | Alarm trigger | Motion detection, Tampering alarm |
| Network & Remote Monitoring | Protocols | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP |
| | System compatibility | ONVIF |
| | CMS | Full function CMS (Central monitoring software) |
| | Mobile Client Application | Supports android and iOS APP for Smart phone and tablets |
| | Bandwidth control | VBR (Automatic) and CBR (Manual) supported |
| | Network storage | CMS/Web |
| Interface | Ethernet | 1 RJ45 10/100 Ethernet port |
| | Power Input | Standard DC Jack |
| | Audio | 1x Audio in |
| Electrical | Power Requirement ($\pm 10\%$) | 12 VDC $\pm 10\%$, PoE (802.3af) |
| | Power Consumption | Max. 7W |
| Environmental | Enclosure | IP66 Weatherproof Outdoor Enclosure |
| | Operating Temperature | -20°C to + 60°C |

TECHNICAL SPECIFICATIONS

VP-NC2615B-AF3IRL3

| | | |
|---------------|---------------|----------------------------|
| Mechanical | Color | White |
| | Dimension | 182(W) x 66(H) x 67.5(D)mm |
| | Weight | 850g |
| Certification | Certification | UL, CE, FCC, RoHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

