



# HIGH DEFINITION 2MP IP DOME CAMERA

# VP-NC2692D-Z2IR1P1L3 IR NIGHT VISION MOTORIZED CAMERA



## FEATURES

High Definition 2MP (1920 x 1080) resolution

1/2.8" Progressive Scan CMOS Sensor

Inbuilt 4pcs. Smart Array LEDs with intensity control

High performance IR Cut mechanical filter for True Day & Night vision

Inbuilt 3D DNR & BLC functions

Onvif supported



## TECHNICAL SPECIFICATIONS

### VP-NC2692D-Z2IR1P1L3

Camera	Image sensor	1/2.8" Progressive Scan CMOS Sensor
	Signal System	PAL/NTSC
	Effective Pixels	1920 (H) × 1080 (V)
	Minimum Illumination	Color : 0.05Lux @ F1.2, 0.01 lux @ F1.4, B&W: 0 Lux at IR on
	Electronic Shutter Speed	1/25s (1/30s) ~ 1/10,000s
	Gain Control	Auto
	White Balance	Auto
	Signal to Noise	> 52 dB
	Auto Iris	DC Drive
Lens	Lens Type	2.7 mm to 13.5mm Lens
	Focus	Auto/Manual
	Lens Type	Motorized
Day/Night Functionality	Day & Night	True Day & Night with ICR
	IR Cut	High performance Mechanical IR Cut Filter with auto switch
	IR Source	Inbuilt 4Pcs Smart Array LEDs with intensity control
	IR Range	30 Mtr.
Compression	Video compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
	H.265 codec profile	Main profile
	Video Bit Rate	32 Kbps ~ 16 Mbps
Resolution and Frame Rate	Max. Resolution	1920 × 1080
	Main Stream	50Hz: 25fps (1920x1080), 25fps (1280 × 960), 25fps (1280 × 720), 25fps (704 × 576), 25fps (640 × 480) 60Hz: 30fps (1920x1080), 30fps (1280 × 960), 30fps (1280 × 720), 30fps (704 × 576), 30fps (640 × 480)
	Sub / Third Stream	25fps (740 × 480), 25fps (704 × 576), 25fps (640 × 480)
Operational Features	Privacy masking	Support up to 3 zones
	WDR	Supported
	Defog	Supported
	Backlight compensation	Supported
	Codec streaming capability	Triple streaming
	DNR	Inbuilt 3D DNR (Digital Noise Reduction) circuit
	Image settings	Saturation, Brightness, Chroma, Contrast, White Balance Sharpen, Mirror, 3D NR, FLK( Flicker control) etc. Adjustable through client software or web browser
	Security	User Authentication
	Motion Detection	Supported
	Alarm trigger	Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login
Network & Remote Monitoring	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP IPv4, IPv6
	System compatibility	Support ONVIF 2.4
	CMS	Full function CMS ( Central monitoring software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	CBR/VBR
Network storage	NVR/CMS	

## TECHNICAL SPECIFICATIONS

### VP-NC2692D-Z2IR1P1L3

Interface	Ethernet	
	Power Input	Standard DC Jack
Electrical	Power Requirement	12 VDC $\pm$ 10% , PoE (IEEE 802.3af)
	Power Consumption	Max. 5W
Environmental	Enclosure	IP 66 Weather proof outdoor enclosure
	Mounting bracket	Up to IK10
	Impact Protection	Integrated mounting bracket with cable management
	Operating Temperature	-20°C to + 55°C
	Operating Humidity	95% or less (non-condensing)
Mechanical	Color	White
	Dimension	$\Phi$ 119 x 98(H) mm
	Weight	800g
Certification	Certification	UL, CE, FCC, RoHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: [sales@vantagesecurity.com](mailto:sales@vantagesecurity.com)

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

