

# FULL HIGH DEFINITION 4MP IP DOME CAMERA

## VP-NC81114D-F3IR1S9 IR NIGHT VISION FIXED DOME CAMERA



### FEATURES

Full High Definition 4MP (2592×1520) resolution

1/2.8" Progressive Scan CMOS Sensor

Triple-Stream(H.265,H.264,MJPEG) supported

High performance IR Cut mechanical filter for True & Night Vision

Inbuilt 120dB True WDR , 3D DNR, ROI, HLC & Defog functions

Smart IR with intensity control

Onboard SD card slot up to 128GB support

IP66 Water proof Indoor enclosure



## TECHNICAL SPECIFICATIONS

# VP-NC81114D-F3IR1S9

|                             |                            |   |
|-----------------------------|----------------------------|---|
| Camera                      | Image sensor               | 1/2.8" Progressive Scan CMOS Sensor   |
|                             | Signal System              | PAL/NTSC  |
|                             | Effective Pixels           | 2592 (H) × 1520 (V)   |
|                             | Minimum Illumination       | Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR   |
|                             | Electronic Shutter Speed   | 1/5 s to 1/100,000 s  |
|                             | Gain Control               | Auto  |
|                             | White Balance              | Auto  |
|                             | Signal to Noise            | >52 dB  |
| Lens                        | Lens Type                  | 3.6mm fixed lens  |
|                             | Lens Mount                 | M12   |
|                             | Focus                      | Fixed   |
|                             | Digital Zoom               | Supported   |
| Day/Night Functionality     | Day & Night                | True Day & Night with ICR   |
|                             | IR Cut                     | High performance Mechanical IR Cut Filter with auto switch  |
|                             | IR Source                  | Inbuilt Smart IR LEDs with intensity control  |
|                             | IR Range                   | Up to 30 Mtr  |
| Compression                 | Video compression          | H.265, H.264, MJPEG   |
|                             | H.265 codec profile        | Main profile  |
|                             | Video Bit Rate             | 256 Kbps ~ 8 Mbps   |
| Resolution and Frame Rate   | Max. Resolution            | 2592 × 1520   |
|                             | Frame rate                 | 50Hz: 25 fps (2592 × 1520, 2304 × 1296, 1920 × 1080)<br>60Hz: 30 fps (2592 × 1520, 2304 × 1296, 1920 × 1080)                            |
|                             | Third Stream               | 50Hz: 25 fps (1280 × 720, 640 × 360, 352 × 288)<br>60Hz: 30 fps (1280 × 720, 640 × 360, 352 × 240)                                      |
| Operational Features        | Wide Dynamic Range (WDR)   | 120dB   |
|                             | Privacy Masking            | Supported, 4 zone selectable  |
|                             | DNR                        | Inbuilt 3D DNR (Digital Noise Reduction) circuit  |
|                             | Codec streaming capability | Triple streaming  |
|                             | ROI                        | 4 zone supported  |
|                             | HLC                        | Supported   |
|                             | Defog                      | Supported   |
|                             | Image Settings             | Support rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser and client software                 |
|                             | Security                   | Heartbeat, Flash-prevention, dual stream, Password Protection, Privacy Mask, IP Address Filter, User authentication (Multiple IDs )     |
|                             | Alarm Trigger              | Motion Detection, Tampering Alarm, Network Disconnected, IP Address Conflict, Illegal Login, HDD full, HDD error                        |
| Network & Remote Monitoring | Protocols                  | TCP / IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour |
|                             | System Compatibility       | ONVIF (PROFILE S, PROFILE G)  |
|                             | CMS                        | Full function CMS ( Central monitoring software), Firmware upgrade through web browser  |
|                             | Mobile Client Application  | Supports android and iOS APP for Smart phone and tablets  |
|                             | Bandwidth Control          | VBR (Automatic) and CBR (Manual) supported  |

## TECHNICAL SPECIFICATIONS

# VP-NC81114D-F3IR1S9

|                   |                       |   |
|-------------------|-----------------------|---|
| Interface         | Ethernet              | 1 RJ45 10/100 Ethernet port   |
|                   | Power Input           | Standard DC Jack  |
| Analytics Feature | Smart Features        | Perimeter Intrusion, Line Crossing, Stationary Object, Face detection, cross counting |
| Electrical        | Power Requirement     | 12 VDC $\pm$ 25% , PoE (802.3af)  |
|                   | Power Consumption     | Max. 6W   |
| Environmental     | Enclosure             | IP 67 Weather proof enclosure   |
|                   | Operating Temperature | -30°C to + 60°C   |
|                   | Operating Humidity    | 95% or less (non-condensing)  |
| Mechanical        | Color                 | White   |
|                   | Dimensions            | $\Phi$ 110 x 85.4 mm  |
|                   | Weight                | 390g  |
| Certifications    | Certifications        | UL, CE, FCC, RoHS   |

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

## DIMENSIONS

Unit: mm

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

