

HIGH PERFORMANCE NETWORK VIDEO RECORDER

VP-NV5208-1SX1 8 CHANNEL NVR



FEATURES

- ONVIF Supported
- Up to 4 Megapixels Resolution Display and Recording
- HDMI and VGA output at up to 1920×1080P resolution
- Full function CMS (Central monitoring software) supported
- Supports line crossing and intrusion detection
- Smart playback to improve the playback efficiency
- Supports Intelligent 3D positioning for IP PTZ camera
- Supports remote monitoring on Mobile Client (Android, IOS) and IE

H.265+
COMPRESSION



**Motion
Detection**



**Network Video
Monitoring
Software**



**E-mail
Alert**



**Mobile
Monitoring**

TECHNICAL SPECIFICATIONS

VP-NV5208-1SX1

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	User interface:	Support 16-bit true color graphical menu interface and mouse operation
Bandwidth	Incoming Bandwidth	60 Mbps
	Outgoing Bandwidth	60 Mbps
Interface	IP Video Input	8-ch
	HDMI/VGA output	1920 x 1080p/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
	Video Compression	H.265+/H.265/ H.264+/H.264
	Network	1 x (10/100) ethernet port (RJ45)
	USB	2 x USB 2.0
Resolution & Frame Rate	Recording Resolution	4 MP/3 MP/1080p/720p/4CIF/DCIF/ 2CIF/CIF/QCIF
	Playback Resolution	4 MP/3 MP/1080p/720p/4CIF/DCIF/ 2CIF/CIF/QCIF
	Max playback capability	Max 8 ch playback
	Capability	1-ch @ 4 MP / 2-ch @ 1080p
Network & Remote Monitoring	Protocols	TCP/IP, DHCP,DNS, DDNS, NTP, SADP, SMTP,UPnP
	DDNS	Supported; Dynamic and Static IP support
	CMS	Full function CMS (Central Monitoring Software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	VBR (Automatic) and CBR (Manual) supported
Features	Security	Password protection, user management
	Playback Function	Fast forward / backward
	Search Mode	Time/Date, Alarm, Motion Detection & smart Search
	Alarm Notifications	FTP, Email notification supported
Recording & Storage	Smart Analytics	Line crossing and intrusion detection supported
	Recording Mode	Manual/Motion Detection/Continuous
	Storage	1 SATA port up to 6TB
	Overwrite Mode	Supported
General	Power Supply	12 VDC
	Power Consumption	<10W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	90% or less (non condensing)
	Chassis	Standalone 1U chassis
	Dimensions	260 x 225 x 48 mm
Certification	Weight	≤ 1 kg (without hard disk)
	Certifications	CE, FCC, RoHS

*Actual product and specifications may differ from the images appearing in the brochure and are subject to change without notice due to ongoing product development.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-214012, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, iso 14001:2004 CERTIFIED COMPANY)

