




IMAGING & SCREENING SECURITY SYSTEM

VP-XR6550-BSS16

X-RAY BAGGAGE SCANNER





FEATURES

X-ray generator with 4 color displaying technology for efficient security

Dual energy penetration system supports high/low density and organic/inorganic discerning

Auto-inspection of drugs and explosives

Supports real-time storage and retrieval of scanned images

System initiates auto-diagnostic and calibration automatically at power on

Suitable for scanning mid-sized baggage at airports, bus/ train/metro stations, borders/immigration security check points

Energy saving & environment protective design


VP-XR6550-BSS16


| | T 10: | CEO 4/M/ |
|--------------------------|-------------------------------------|--|
| X-Ray Generator | Tunnel Size | 659.4(W) × 503.85(H)mm |
| | Wire Resolution | Typical 40 AWG |
| | Steel Penetration | Typical 32mm |
| | Spatial Resolution | Vertical:1.0mm, horizontal:1.0mm(top view) |
| | Penetration | 30mm(top view); 30mm(side view) |
| | Resolution of Organic Matter | 1 - 120 mm |
| | Grayscale and Mixture Resolution | 1 - 40mm |
| | Resolution of Inorganic Objects | 0.2-14mm |
| | X-Ray Dosage Each Inspection | ≤ 4.8 μSv(uGy) |
| | X Ray Generator | 160KV |
| | Boundary Leakage | \leq 0.5 μ Sv /h(uGy/h) |
| | S/N Ratio | <60dB |
| | Conveyor Speed | 0.2m/s |
| | Conveyor Max Load | 180kg |
| | Power Consumption | 0.5KW |
| | Leakage Current | ≤5.0mA |
| | Cooling | Sealed oil cooling |
| | Duty Cycle | 100% |
| | Film Safety | Guarantee ASA/ISO1600 Film |
| | Storage Capacity | Up to 10,000 images stored automatically. |
| Configuration | Operation System | LINUX |
| | Display | 21.5" LED screen, resolution: 1280x1024 pixels |
| | Operation Console | Available (optional) |
| | Computer | Hard drive: 500, Storage : 1G |
| | Electric Roller | One-phase |
| Power & Environmental | Working Temperature /Humidity | 5 °C ~ 40°C/ 0%-90%(non-condensing) |
| | Storage Temperature /Humidity | -20°C-60°C /10%-90%(non-condensing) |
| | Working Voltage | AC220V(±10%-15%) 50±3Hz |
| Mechanical | Dimensions | 2808.45x902x1362.5mm (L × W × H) |
| | Net Weight | 450kg |
| Certifications | Certifications | CE, FCC,RoHS |

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

DIMENSIONS

Unit: mm





VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001: 2008, ISO 14001: 2004 CERTIFIED COMPANY)





