

HIGH DEFINITION 4 IN 1 DOME CAMERA

VV-AC5M54D-M04F3L3 5MP IR Night Vision Varifocal Camera



FEATURES

5 Megapixel HD resolution (2592x1944 pixels)

1/2.5" Progressive Scan CMOS sensor

4 in 1 (AHD/TVI/CVI/CVBS) camera, UTC supported



Inbuilt IR LEDs for 30 mtr IR range

High performance IR Cut mechanical filter for True Day & night vision

3.6mm lens

High performance IR with intensity control

Supports WDR/ Auto White Balance/ Gain Control/ Noise reduction



TECHNICAL SPECIFICATIONS

WV-AC5M54D-M04F3L3

| | | |
|-------------------------|----------------------------------|--|
| Camera | Image sensor | 1/2.5" Progressive Scan CMOS Sensor |
| | Signal System | PAL/NTSC |
| | Effective Pixels | 2592 (H) x 1944 (V) |
| | Frequency | 50 Hz (PAL) / 60 Hz (NTSC) |
| | Image Resolution | 5 Megapixel |
| | Minimum Illumination | Color: 0.1 Lux at F1.4 , B/W: 0 Lux at IR on |
| | Signal to Noise | > 50 dB |
| | Shutter Time | 1/25s~1/50,000s |
| | Angle Adjustment | Pan 0-360°, Rotate 0-360°, Tilt 0-90° |
| | White Balance | Auto / Manual |
| Lens | Lens Type | 3.6mm lens |
| | Lens Mount | M12 |
| | Focus | Fixed |
| Day/Night Functionality | Day & Night | True Day & Night with ICR |
| | IR Cut | High performance Mechanical IR Cut Filter with auto switch |
| | IR Source | High performance IR LEDs with intensity control |
| | IR Range | Up to 20 Mtrs |
| Operational Features | Wide Dynamic Range (WDR) | DWDR |
| | Picture Adjustment | Supported |
| | OSD Menu | Supported |
| Interface | Video Output | AHD / TVI / CVI/ CVBS Video output |
| | Power Input | Standard DC Jack |
| Electrical | Power Requirement ($\pm 10\%$) | DC 12V ($\pm 10\%$) |
| | Power Consumption | Max 5 W with IR on |
| Environmental | Enclosure | IP66 Weatherproof Indoor Enclosure |
| | Mounting bracket | Integrated mounting bracket with cable management |
| | Operating Temperature | -10°C to + 50°C |
| | Operating Humidity | 95% or less (non-condensing) |
| Mechanical | Color | White |
| | Dimensions | ∅ 90.5 x80(H) mm |
| | Weight | 300g |
| Certification | Certification | CE, FCC, RoHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

