

FULL HIGH DEFINITION

2MP 4 IN 1 BULLET CAMERA

VV-AC8452P-Z10IR5B1

Mini Pan Tilt Zoom Camera



FEATURES

2 Megapixel Full HD 1080p Resolution

1/2.7" Progressive Scan CMOS Sensor

10x Optical zoom



220° Panning range

Inbuilt Array IR range up to 100 mtrs

Inbuilt 3D DNR & BLC functions

Supports presets/pattern/ scan

IP66 Weather proof Outdoor Enclosure



TECHNICAL SPECIFICATIONS

WV-AC8452P-Z10IR5B1

Camera	Image sensor	1/2.7" Progressive Scan CMOS Sensor
	Signal System	PAL/NTSC
	Effective Pixels	1920 (H) x 1080 (V)
	Frequency	50 Hz (PAL) / 60 Hz (NTSC)
	Horizontal Resolution	2 Megapixel
	Minimum Illumination	Color : 0.01Lux @ F1.2, B&W: 0.0015 lux @ F1.4,0 Lux at IR on
	Signal to Noise	> 50 dB
	Gain Control	Auto / Manual / Off
	White Balance	Auto/ Manual / Indoor/ Outdoor
	DNR	Inbuilt 2D/ 3D DNR (Digital Noise Reduction) circuit
	Iris	Auto Iris
	Electronic Shutter Speed	1/50 ~ 1/10000s
Lens	Lens Type	5.1mm ~ 51mm
	Angle of View	55.2-7.3 degree (Wide-Tele)
	Focus	Auto Focus/ Manual Focus
	Zoom	10x Optical Zoom
	Zoom Speed	Approx 2s (Optical Wide-Tele)
Day/Night Functionality	Day & Night	True Day & Night with ICR
	IR Cut	High performance Mechanical IR Cut Filter with auto switch
	IR Source	Inbuilt 4 PCS Array IR + 2 PCS Laser LED
	IR Range	Up to 100 Mtrs
Pan-Tilt	Pan Angle	0° to 220°
	Tilt Angle	45° to 40°
	Pan Speed	0° ~ 30°/s
	Tilt Speed	0° ~ 25°/s
	Presets	220
	Dwell Time	1-60s
	Scan	Any point in range:-45°~40° and 0°~200°
	Patrol	3 Patrols, up to 16 presets per patrol
	PTZ position display	Supported
Operational Features	OSD Menu	Supported
	Camera ID	On/Off
	Motion Detection	Supported
	BLC	Supported
	Video Adjustment	Supported
	WDR	D-WDR
	Protocols	PELCO-P, PELCO-D, Multi protocol support
	Baud Rate	2400/4800/9600bps
Interface	Power Input	Standard DC Jack / 2Pin Wired Terminal
	Data Communication	RS-485
	Video Output	1 BNC Video Output (AHD/TVI/CVI/CVBS selectable)
Electrical	Power Requirement	12VDC/2A (± 10%)
	Power Consumption	Max 15 W

TECHNICAL SPECIFICATIONS

VV-AC8452P-Z10IR5B1

Environmental	Enclosure	IP66 Weather proof outdoor enclosure
	Mounting bracket	External Mounting bracket included (Optional)
	Operating Temperature	-40°C to +60°C
	Operating Humidity	95% or less (non-condensing)
Mechanical	Color	White
	Dimension	184x100mm
Certifications	Certifications	CE, FCC, RoHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

