

ACCESS & TIME MANAGEMENT SYSTEM

VV-BS400FP-CAA14

STANDALONE INTEGRATED FINGERPRINT READER WITH CARD READER



FEATURES

Multiple Identification Modes with fingerprint and RFID authentication for access control and attendance management

High Storage Capacity upto 3,000 users and 70,000 transaction records

Equipped with High-reliability optical fingerprint collector for reliable recognition performance

Linkage and integration with video recording or snapshot capture via NVMS Unified software

Supports real-time logs and event monitoring

TECHNICAL SPECIFICATIONS

WV-BS400FP-CAA14

Parameter	Specifications
Recognition Method	Fingerprint, RFID (optional MIFARE)
User Capacity	3,000 users
Record Capacity	70,000 records
Communication	TCP/IP
Fingerprint Sensor	Industrial-grade optical fingerprint collector
False Acceptance Rate	< 0.0001%
Refusal Rate	< 0.01%
Wiegand Interface	1 x Wiegand 26-34
Exit Button Input	1
Door-Contact Input	1
Alarm Input	1
Alarm Output	1
Lock Control Output	1
Power Supply	DC 12V \pm 10%, 1A
Working Temperature	-10°C~45°C
Operating Humidity	20% - 60%
Dimension	122 x 77 x 45 mm
Certifications	CE, FCC, RoHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

