




ACCESS & TIME MANAGEMENT SYSTEM

VV-BS510FP-CT5

FINGERPRINT BASED STANDALONE SYSTEM





2.4" Color







FEATURES

Scratch Proof optical sensor

360° verification angle

2.4" Color LCD screen

USB connectivity for communication & data backup

High performance sensing with < 1s identification time

VV-BS510FP-CT5

Hardware & Platform	CPU	32 bit Microprocessor
	Memory	64M RAM, 256M Flash
	Sensor	Scratch proof High performance optical sensor
	Sensor area	16mm x 14mm
	OS	Embedded Linux OS
	Operation mode	Offline
	Display	2.4" Color LCD screen
	Keypad	Alpha-numeric backlit keypad
	Indicators	Audio visual indication
Operation Capacity	Fingerprint templates	1000 users
	Card Ids	1000 users
	Password user	1000 users
	Transaction capacity	100000 logs
Verification	Verification angle	360° verification angle
	FAR	< 0.0001%
	FRR	<0.0 1%
	Verification time	< 1s
	Algorithm	Advanced Smart finger algorithm BioTH 2.0
	Verification mode	1:1; 1:N
	Authentication modes	Fingerprint only/ Fingerprint + PIN/ Fingerprint + EM Card
Operational Features	Voice notification	Supported
	Real time Clock	Supported
	Card Reader	Inbuilt 125 Khz EM card reader (Mifare reader optional)
	Languages	English
	Card Reader Range	3-5 cms read range
Communication	USB	USB 2.0 for communication and data backup
Power	Power requirement	DC 5V, 1A
Environmental	Operation temperature	-10°- 60°C
	Operating Humidity	Up to 90% (non condensing)
Mechanical	Construction material	ABS plastic
	Dimensions	160mmx130mmx35mm
	Weight	0.87kg
Certifications	Certifications	CE, FCC, ROHS

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001: 2008, ISO 14001: 2004 CERTIFIED COMPANY)





