

ACCESS & TIME MANAGEMENT SYSTEM

WV-BS810FP-CBAZ1

FINGERPRINT TA SYSTEM WITH ACCESS CONTROL & BATTERY BACKUP



FEATURES

- Scratch Proof optical sensor
- High resolution 600 dpi optical sensing
- 360° verification angle
- 3.5" Color LCD screen
- TCP-IP network connectivity
- USB connectivity for communication and data backup
- High performance sensing with < 1s identification time
- Access control functions
- Inbuilt battery backup



3.5" Color
LCD Display



Battery
Backup



TCP/IP



Access
Control



USB

TECHNICAL SPECIFICATIONS

VV-BS810FP-CBAZ1

| | | |
|----------------------|------------------------|------------------------------------------------------------|
| Hardware & Platform | CPU | 32 bit Microprocessor |
| | Memory | 64M RAM, 256M Flash |
| | Sensor | Scratch proof High performance optical sensor |
| | DPI rating | 600 dpi resolution |
| | Sensor area | 16mm x 14mm |
| | OS | Embedded Linux OS |
| | Operation mode | Offline |
| | Display | 3.5" Color LCD screen |
| | Keypad | Alpha-numeric backlit keypad |
| | Indicators | Audio visual indication , with dual color LEDs |
| Operation Capacity | Fingerprint templates | 3000 users |
| | Card Ids | 3000 users |
| | Transaction capacity | 100000 logs |
| Verification | Verification angle | 360° verification angle |
| | FAR | < 0.0001% |
| | FRR | < 1% |
| | Verification time | < 1s |
| | Algorithm | Advanced Smart finger algorithm V 15.0 |
| | Authentication modes | Fingerprint only/ Fingerprint + PIN/ Fingerprint + EM Card |
| Operational Features | Backup Battery | Inbuilt battery backup for upto 6 hours standby time |
| | Real time Clock | Supported |
| | Voice notification | Supported |
| | Card Reader | Inbuilt 125 Khz EM card reader (Mifare reader optional) |
| | Languages | Multi-language support |
| | Card Reader Range | 3-5 cms read range |
| | Door bell function | Supported |
| | Access control support | Door Relay Access control function with NO-NC support |
| | Exit Switch support | Exit switch NO type support |
| | Access Time Zones | 50 Access Time Zones |
| | Function keys | 6 number user defined function keys |
| Communication | Ethernet | TCP/IP 10/100 ethernet interface |
| | USB | USB 2.0 for communication and data backup |
| | RS 485 | Supported |
| | Wiegand | Wiegand in and out |
| Power | Power requirement | DC 12V, 1.5A |
| Environmental | Operation temperature | 0° to 50°C |
| | Operating Humidity | upto 90% (non condensing) |
| Mechanical | Construction material | ABS plastic |
| | Dimensions | 221.7x159.5x42.9mm |
| Certifications | Certifications | CE, FCC, ROHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

