

# HIGH DEFINITION DIGITAL VIDEO RECORDER

## VV-DV3804-1SL3 4 CHANNEL 5 IN 1 DVR



### FEATURES

High performance cloud technology DVR

Pentabrid(AHD +TVI+CVI+Analog+ IP) DVR with NVR functionality & IP camera support

H.265 video Dual Stream compression

Max 1080N resolution @ 25fps supported

HDMI / VGA Video simultaneous video output

Supports remote monitoring on Mobile Client (Android, IOS), IE and through CMS

Inbuilt Motion Recording supported



## TECHNICAL SPECIFICATIONS

# VV-DV3804-1SL3

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	User interface	Support 16-bit true color graphical menu interface and mouse operation
Interface	Video Input	4-ch Composite video 1.0 Vp-p, 75 ohm
	Audio Input	4-ch Line in RCA input (1 k $\Omega$ )
	Video Output	1-ch BNC output
	VGA Video Output	1-ch, Resolution: 1920 x 1080P /50Hz, 1280 x 1024 /50Hz, 1280x720/50Hz, 1024x768/50Hz
	HDMI Video Output	1-ch, Resolution: 1920x1080P/50Hz, 1280x1024/50Hz, 1280x720/50Hz, 1024x768/50Hz
	Audio Output	1-ch, RCA (Linear, 1 k $\Omega$ )
	Communication	RS 485 ( for PTZ and Keyboard )
	Network	1 x RJ45 (10M/100M ) Adaptive Ethernet Interface
	USB	2 x 2.0 USB interface (for backup, firmware upgrade and mouse interface)
Compression	Video compression	H.265/ H.264 dual stream compression
	Audio compression	G.711u/G.711a
Resolution & Frame Rate	Recording	4 ch 1080N @ 25 fps
	Playback	4 ch 1080N @ 25 fps
	Frame Rate	Max 30 fps supported for NTSC, Max 25 fps for PAL
Network & Remote Monitoring	Cloud Monitoring	Supported
	DDNS	Supported; Dynamic and Static IP support
	Protocols Supported	HTTP, IPv4,IPv6, TCP/IP, SMTP, DHCP, DNS, PPPOE, DDNS, NTP, FTP, UPNP
	CMS	Full function CMS ( Central monitoring software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	VBR (Automatic) and CBR (Manual) supported
Features	Simultaneous Playback	Max 4 channel Simultaneous Playback
	Analog Mode	Supported (4 x 1080N AHD/TVI/CVI/CVBS)
	Pentabrid Mode	2 x 1080N (Analog) + 4 x 1080P(IP)
	NVR Mode	Supported (9 x 1080P)
	Multi Screen Display	9 Channel/4 Channel / 1Channel
	Security	Password protection, User management

TECHNICAL SPECIFICATIONS

**WV-DV3804-1SL3**

	Playback Function	Play, Pause, Stop, Fast play, Rewind
	Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
	Privacy Masking	1 Rectangular Zones (Each camera)
	Alarm Notifications	FTP, Email, Recording, Screen tips, Buzzer
	Dual Stream	Supported
	OSD	Camera title, Time, Video loss, Alarm, Motion detection,Recording
Recording & Storage	Recording Mode	Manual/ Alarm/ Motion Detection/ Continuous
	Storage	1 SATA port up to 8TB
	Overwrite Mode	Continuous
General	Power Supply	DC 12V
	Power Consumption	<6W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	90% or less (non condensing)
	Dimensions	260 x 215 x 43mm
	Weight	2kg (without hard disk)
Certifications	Certifications	CE, FCC, ROHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.



**VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED**

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

