

HIGH DEFINITION DIGITAL VIDEO RECORDER

VV-DV3832-8SL3 32 CHANNEL 5 IN 1 DVR



FEATURES

High Performance Cloud Technology DVR

Pentabrid(AHD +TVI+CVI+Analog+ IP) DVR with NVR functionality & IP camera support

H.265 video Dual Stream compression


Max 1080N resolution @ 25fps supported

Gigabit (10/100/1000) network port supported

HDMI / VGA Video simultaneous video output

Supports remote monitoring on Mobile Client (Android, IOS), IE and through CMS

Inbuilt Motion Recording supported



TECHNICAL SPECIFICATIONS

VV-DV3832-8SL3

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	User interface	Support 16-bit true color graphical menu interface and mouse operation
Interface	Video Input	32-ch Composite video 1.0 Vp-p, 75 ohm
	Audio Input	12-ch Line in RCA input (1 k Ω)
	Audio Output	1-ch, RCA (Linear, 1 k Ω)
	VGA Video Output	1-ch, Resolution: 1920 x 1080P /50Hz, 1280 x 1024 /50Hz, 1280x720/50Hz, 1024x768/50Hz
	HDMI Video Output	1-ch, Resolution: 3840x2160/50Hz,1920 x 1080P /50Hz, 1280 x 1024 /50Hz,1280x720 /50Hz,1024 x 768 /50Hz
	Video Output	1-ch BNC output
	Alarm Input/Output	16/4
	Communication	RS485 (for PTZ and Keyboard)
	Network	1 x RJ45 (10M/100M/1000M) Adaptive Ethernet Interface
	USB	2 x 2.0 USB interface (for backup, firmware upgrade and mouse interface)
Compression	Video compression	H.265/ H.264+/ H.264 dual stream compression
	Audio compression	G.711u/ G.711a
Resolution & Frame Rate	Recording	32 ch 1080N @ 25 fps
	Playback	Up to 32 ch
	Frame Rate	Max 30 FPS for NTSC, Max 25 FPS for PAL
Network & Remote Monitoring	Cloud Monitoring	Supported
	DDNS	Supported; Dynamic and Static IP support
	Protocols Supported	HTTP, IPv4/ IPv6, TCP/IP, SMTP, DHCP, DNS, PPPOE, DDNS, NTP, FTP, UPNP
	CMS	Full function CMS (Central monitoring software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	VBR (Automatic) and CBR (Manual) supported
Features	Remote Playback	Up to 4 channel Simultaneous Playback
	Analog Mode	Supported (32 x 1080N AHD/TVI/CVI/CVBS)
	Pentabrid Mode	16x 1080N (Analog) + 16 x 8MP(IP)
	NVR Mode	Supported (32 x 8MP)
	Multi Screen Display	32 Channel/25 Channel/16 Channel/9 Channel/8 Channel/ 4 Channel / 1Channel
	Security	Password protection, User management

TECHNICAL SPECIFICATIONS

WV-DV3832-8SL3

	Playback Function	Play, Pause, Stop, Fast play, Rewind
	Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
	Privacy Masking	3 Rectangular Zones (Each camera)
	Alarm Notifications	FTP, Email, Recording, Screen tips, Buzzer
	Dual Stream	Supported
	OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording & Storage	Recording Mode	Manual/ Alarm/ Motion Detection/ Continuous
	Storage	8 SATA port up to 8TB
	E-SATA	Supported
	Overwrite Mode	Continuous
General	Power Supply	AC 220V
	Power Consumption	<35W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	90% or less (non condensing)
	Dimensions	440 x450 x 95mm
	Weight	9.8kg (without hard disk)
Certifications	Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

