

HIGH DEFINITION

5MP DIGITAL VIDEO RECORDER

VV-DV3904-1SL3

4 CHANNEL 5 IN 1 DVR



FEATURES

- High performance cloud technology DVR
- Pentabrid(AHD +TVI+CVI+Analog+ IP) DVR with NVR functionality & IP camera support
- H.265 video Dual Stream compression
- Max 5MP resolution @ 6fps supported
- Inbuilt Motion Recording supported
- HDMI / VGA video simultaneous video output
- Supports remote monitoring on Mobile Client (Android, IOS),IE and through CMS



TECHNICAL SPECIFICATIONS

VV-DV3904-1SL3

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel recording, playback, network operation, USB backup
	User interface	Supports 16-bit true color graphical menu interface and mouse operation
Interface	Video Input	4-ch Composite video 1.0 Vp-p, 75 ohm
	Audio Input	4-ch Line in RCA input (1 k Ω)
	Video Output	1 HDMI / 1 VGA / 1 CVBS output
	VGA Video Output	1-ch, Resolution: 1920 x 1080P /60Hz, 1280 x 1024 /60Hz, 1280 x 720 /60Hz, 1024 x 768 /60Hz
	HDMI Video Output	1-ch, Resolution: 2560 x 1440/30Hz, 1920x1080P/50Hz 1280x1024/50Hz, 1280x720/50Hz, 1024x768/50Hz
	Audio Output	1-ch, RCA (Linear, 1 k Ω)
	Communication	RS485 (for PTZ and Keyboard)
	Network	1 x RJ45 (10M/100M) Adaptive Ethernet Interface
	USB	2 x 2.0 USB interface (for backup, firmware upgrade and mouse interface)
Compression	Video compression	H.265/H.265+/H.264/ (1~25fps) dual stream compression
	Audio compression	G.711u/ G.711a
Resolution & Frame Rate	Recording	Analog: PAL:5MP(2592x1944 4*6fps),5MP_HALF(1296x1944 4*10fps), 4MP(2560x1440 4*8fps),4MP_HALF(1280x1440 4*15fps),3MP (2048x1536 4*9fps),1080P(1920x1080 4*15fps),720P(1280x720 4*25fps), 960H(960x576 4*25fps) Pure IP: PAL: 5MP@5x25fps,4MP@7x25fps,3MP@7x25fps,1080P@12x25fps,960P@16x25fps,720P@16x25fps,D1@16x25fps
	Playback	Pure Analog: 4CH 5M@6fps, 4CH 4M@7fps, 4CH 3M@9fps, 4CH 1080p@15fps Mix Mode: 3CH 1080p@15fps, 1CH 5M@6fps, 1CH 4M@7fps, 1CH 3M@9fps Pure IPC: 1CH 5MP@30fps, 1CH 4MP@30fps, 1CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps
	Frame Rate	Max 25 fps @ 720p
Network & Remote Monitoring	Cloud Monitoring	Supported
	DDNS	Supported; Dynamic and Static IP support
	Protocols Supported	HTTP, IPv4,IPv6, TCP/IP, SMTP, DHCP, DNS, PPPOE, DDNS, NTP, FTP, UPNP
	CMS	Full function CMS (Central monitoring software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	VBR (Automatic) and CBR (Manual) supported
Features	Simultaneous Playback	Max 4 channel Simultaneous Playback
	Analog Mode	Analog: 4*(TVI/AHD: 5M; AHD/TVI/CVI: 4M; AHD/TVI: 3M; AHD/TVI/ CVI: 1080P/720P; Analog: 960H)
	Pentabrid Mode	Analog+IP: 2*Analog(1080P)+7*IP (MAX 5MP)
	NVR Mode	IP: 16*5MP/4MP/3MP/1080P/960P/720P (Total bandwidth \leq 50M)
	Multi Screen Display	4 Channel / 1 Channel
	Security	Password protection, User management

TECHNICAL SPECIFICATIONS

WV-DV3904-1SL3

	Playback Function	Play/ Pause/ Stop/ Fast play/ Rewind
	Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
	Privacy Masking	1 Rectangular Zones (Each camera)
	Alarm Notifications	FTP, Email, Recording, Screen tips, Buzzer
	Dual Stream	Supported
	OSD	Camera title, Time, Video loss, Alarm, Motion detection,Recording
Recording & Storage	Recording Mode	Manual/Alarm/Motion Detection/Continuous
	Storage	1 SATA port up to 8TB
	Overwrite Mode	Supported
General	Power Supply	DC 12V
	Power Consumption	<6W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	90% or less (non condensing)
	Dimensions	260 x 215 x 43mm
	Weight	2kg (without hard disk)
Certifications	Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

