



# HIGH DEFINITION

**5MP DIGITAL VIDEO RECORDER** 

## VV-DV3908-1SL3

8 CHANNEL 5 IN 1 DVR





#### **FEATURES**

High performance cloud technology DVR

Pentabrid(AHD +TVI+CVI+Analog+ IP) DVR with NVR functionality & IP camera support

H.265 video Dual Stream compression

Max 5MP resolution @ 6fps supported

Inbuilt Motion Recording supported

HDMI / VGA video simultaneous video output

Supports remote monitoring on Mobile Client (Android, IOS), IE and through CMS











### VV-DV3908-1SL3

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel recording, playback, network operation, USB backup
	User interface	Support 16-bit true color graphical menu interface and mouse operation
Interface	Video Input	8-ch Composite video 1.0 Vp-p, 75 ohm
	Audio Input	4-ch Line in RCA input (1 kΩ)
	Video Output	1 HDMI / 1 VGA / 1 CVBS output
	VGA Video Output	1-ch, Resolution: 1920 × 1080P /30Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
	HDMI Video Output	1-ch, Resolution: 2560 x 1440/30Hz,1920×1080P/60Hz,1280x 1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
	Audio Output	1-ch, RCA (Linear, 1 kΩ)
	Communication	RS 485 ( for PTZ and Keyboard )
	Network	1 x RJ45 (10M/100M ) Adaptive Ethernet Interface
	USB	2 x 2.0 USB interface (for backup, firmware upgrade and mouse interface)
Compression	Video compression	H.265/H.265+/H.264/ (1~25fps) dual stream compression
	Audio compression	G.711u/ G.711a
Resolution & Frame Rate	Recording	Analog: PAL:5MP(2592×1944 4*6fps),5MP_HALF(1296×1944 4*10fps 4MP(2560×1440 4*8fps),4MP_HALF(1280×1440 4*15fps),3MP (2048×1536 4*9fps),1080P(1920×1080 4*15fps),720P(1280×720 4*25fps), 960H(960×576 4*25fps)  Pure IP: PAL: 5MP@5×25fps,4MP@7×25fps,3MP@7×25fps,1080P@ 12×25fps,960P@16×25fps,720P@16×25fps,D1@16×25fps
	Playback	Pure Analog: 8CH 5M@6fps, 8CH 4M@7fps, 8CH 3M@9fps, 8CH 1080p@15fps Mix Mode: 4CH 5M@6fps, 4CH 4M@7fps, 4CH 3M@9fps, 4CH 1080P@ 15fps, 1CH 8MP 30fps, 2CH 5MP 30fps, 2CH 4MP fps, 2CH 3MP@30fps Pure IP: 1CH 8MP@30fps, 2CH 5MP@30fps, 2CH 4MP@30fps, 3CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps, 4CH 960P@30fps, 4CH 960P@
	Frame Rate	Max 25 fps @ 720p
Network & Remote Monitoring	Cloud Monitoring	Supported
	DDNS	Supported; Dynamic and Static IP support
	Protocols Supported	HTTP, IPv4/IPv6, TCP/IP, SMTP, DHCP, DNS, PPPOE, DDNS, NTP, FTP, UPNP
	CMS	Full function CMS ( Central monitoring software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	VBR (Automatic) and CBR (Manual) supported
Features	Simultaneous Playback	Max 4 channel Simultaneous Playback
	Analog Mode	Analogue: 8*(TVI/AHD: 5M; AHD/TVI/CVI: 4M; AHD/TVI: 3M; AHD/TVI CVI: 1080P/720P; Analog: 960H)
	Pentabrid Mode	Analogue+IP: 6*Analogue(1080P)+4*IP (Max 8MP) 4*Analog (1080P)+8*IP(Max 8MP),2*Analog(1080P)+12*IP (Max 8MP)
	NVR Mode	IP: 16*8MP/5MP/4MP/3MP/1080P/960P/720P (Total bandwidth ≤80M)
	Multi Screen Display	9 Channel/4 Channel / 1 Channel
	Security	Password protection, User management

#### VV-DV3908-1SL3

	Playback Function	Play/ Pause/ Stop/ Fast play/ Rewind
	Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
	Privacy Masking	1 Rectangular Zones (Each camera)
	Alarm Notifications	FTP, Email, Recording, Screen tips, Buzzer
	Dual Stream	Supported
	OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording & Storage	Recording Mode	Manual/Alarm/Motion Detection/Continuous
	Storage	1 SATA port up to 8TB
	Overwrite Mode	Supported
General	Power Supply	DC 12V
	Power Consumption	<6W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	90% or less (non condensing)
	Dimensions	260 x 215 x 43mm
	Weight	2kg (without hard disk)
Certifications	Certifications	CE, FCC, ROHS

<sup>\*</sup>Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com





(AN ISO 9001: 2008, ISO14001: 2004 CERTIFIED COMPANY)

