



HIGH PERFORMANCE

AHD MOBILE DIGITAL VIDEO RECORDER

VV-DVM6604-HGP1T8 4 CHANNEL VEHICLE DVR





FEATURES

Supports 4CH HD 720P AHD real-time recording

Supports Max 128GB SD card

H.264 video format, Linux system, dual stream

Supports remote download and playback function via $\ensuremath{\mathsf{VMS}}$

12V-36V wide range voltage supply with dedicated battery powered through vehicle











VV-DVM6604-HGP1T8

| System | Operating System | Embedded Linux Operating System |
|------------------------|----------------------|---|
| | Multiplex Operations | Simultaneous multi-channel real-time recording playback |
| | User interface | Support 16-bit true color graphical menu interface |
| | Password security | User password and Administrator password |
| Video | Video Input | 4CH aviation connector |
| | Video output | 1ch VGA video output, 1ch aviation AV output |
| | Video display | 1ch full screen/4ch split screen |
| | Signal system | PAL: 25 FPS; NTSC: 30FPS |
| | Total resources | 720P PAL: 100FPS, NTSC : 120 FPS |
| Audio | Audio Input | 4CH aviation connector |
| | Audio output | 1ch VGA AV output, 1ch aviation AV output |
| | Compression format | G.726 |
| Recording & Storage | Video compression | H.264 Main profile |
| | Image resolution | 720P /960H/D1/CIF |
| | Recording quality | 720P /960H/D1/CIF |
| | Video bit rate | 1024Kbps~4Mbps (each channel) |
| | Playback | 4ch@720P |
| | Audio bit rate | 8K Byte /s/ channel |
| | Storage | 2.5inch SATA hard disk×1, Max 2TB / SD Card max 256 GB (Optional) |
| Alarm | Alarm input | 4CH alarm input |
| | Alarm output | 1 channel |
| | Motion detection | High/Middle/Low sensitivity adjustable |
| Communication ports | USB | The front panel used for files backup and firmware upgrading |
| Software | PC playback | Video playback and analysis by PC client |
| | VMS | Wireless realtime video & audio monitoring, positioning |
| | Software Upgrade | Support SD card memory upgrade |
| | | |

VV-DVM6604-HGP1T8

| Interface | Power supply | DC +6V~+36V |
|----------------|----------------------|-----------------------------|
| | Output voltage | 5V, 300mA |
| | Enclosure | IP54 |
| | Video output voltage | 1.0vp-p, 75Ω |
| | I/O port | High level alarm 5~24V |
| | Operation | -20° C∼ 70° C |
| | Dimensions | 162 x 153 x 52 mm |
| | Weight | 1.90 Kg |
| Certifications | Certifications | CE, FCC, ROHS |

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom Ph:+44-1902793383, Email: sales@vantagesecurity.com

TAF TO PARTIE TO THE TOTAL TOTA



(AN ISO 9001: 2008, ISO14001: 2004 CERTIFIED COMPANY)

