

GUARD MONITORING SYSTEM

VV-GM200RF-CJ2

RF GUARD MONITORING SYSTEM



FEATURES

Auto induction card-reading

Read EM/ID signal card

USB communication, no need downloader station

Super storage capacity 4Mb Flash, 60000 records

Metal Body, Molded rubber shell, super durability

Easy carrying, brilliant exterior design

Sabotage absorbent, easy maintenance

Real time internal clock

Completely water resistant

Reading distance $\leq 10\text{cm}$



USB
Communication



LED



Buzzer
Sound



Water
Resistant



Inbuilt
Battery

TECHNICAL SPECIFICATIONS

VV-GM200RF-CJ2

Parameter	Specifications
Physical	Metal Body, Molded rubber shell, completely water resistant,
Dimensions	150mmx 42mmx 32mm
Frequency	125KHz
Operating Temperature	50deg to 186deg F (- 45deg to + 85deg C)
Memory	4Mb Flash ROM
Humidity	10% to 98% non-condensing Storage
Storage Capacity	60000 records
Battery	3.0 V Lithium Battery, 1200mAh
Signal Card Detection	Auto induction card-reading
Card Reading Distance3cm	5cm (EM signal card)
Communication	USB
Weight	191g
Protection level	IP67 Standard, for tags IP66 standard
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

