



METAL DETECTORS W-MD18Z-DFPU2

DOOR FRAME METAL DETECTOR





FEATURES

Digital pulse technology

High sensitivity 18 zones detection

Anti-interference modular design

Number counts on panel display

Password protected operation

Self calibration after restart

High density fire resistant material

TECHNICAL SPECIFICATIONS

VV-MD18Z-DFPU2

Parameter	Specifications
Detection Zones	18 zones covering full height of walk through passage
Construction	Portable ABS coated panel
Passage Dimension	Height: 2200mm approx. Breadth: 860mm approx
Display	LED digital control panel, real-time statistics & alarm number counts
Alarm	LED indicators & buzzer
Sensitivity	Adjustable sensitivity for different applications
Calibration	Automatic
Detection Level	Uniform from top to bottom
Throughput rate	25 people per minute
Multiple Metal	It can detect multiple objects of various size in all the zones simultaneously
Protection	Conforms to relevant electric safety standard
Power Supply	AC100-220V
Working Environment	-20° C -50° C
Working Frequency	4KHz - 8KHz
Machine Weight	Approx. 70Kg
Dimensions	2200mm (height) x 860mm (width) x 480mm (depth)
Certifications	CE, FCC, RoHS

^{*}Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com



(AN ISO 9001: 2008, ISO14001: 2004 CERTIFIED COMPANY)

