

METAL DETECTORS

VV-MD24Z-DFPU2 DOOR FRAME METAL DETECTOR



FEATURES

- Digital pulse technology
- High sensitivity 24 zones detection
- Anti-interference modular design
- Number counts on panel display
- Password protected operation
- Self calibration after restart
- High density fire resistant material

TECHNICAL SPECIFICATIONS

VV-MD24Z-DFPU2

| Parameter | Specifications |
|---------------------|--|
| Detection Zones | 24 zones covering full height of walk through passage |
| Construction | Portable ABS coated panel |
| Passage Dimension | Height: 2010mm approx. Breadth: 700mm approx |
| Display | LED digital control panel, real-time statistics & alarm number counts |
| Alarm | LED indicators & buzzer |
| Sensitivity | Adjustable sensitivity for different applications |
| Calibration | Automatic |
| Detection Level | Uniform from top to bottom |
| Throughput rate | 25 people per minute |
| Multiple Metal | It can detect multiple objects of various size in all the zones simultaneously |
| Protection | Conforms to relevant electric safety standard |
| Power Supply | AC85-264V |
| Working Environment | -20°C -50°C |
| Working Frequency | 4KHz - 8KHz |
| Machine Weight | Approx. 70Kg |
| Dimensions | 2200mm (height) x 800mm (width) x 580mm (depth) |
| Certifications | CE, FCC, RoHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

