

ULTRA HIGH DEFINITION 6MP IP BULLET CAMERA

VV-NC41336B-F3WLIRT1
FULL COLOR DUAL ILLUMINATION FIXED CAMERA



COLOR ON
CAMERAS

FEATURES

Ultra high definition 6MP(3200 x 1800) resolution

1/2.7" progressive scan CMOS sensor

Dual night vision modes with smart IR LED and white LED supplementary light

High performance IR cut mechanical filter for true day & night vision

Inbuilt Digital WDR, 3D DNR, HLC, BLC & ROI functions

Support dual streams

Support remote monitoring by smart phones & tablet PCs with iOS and Android OS

IP67 weather proof enclosure



TECHNICAL SPECIFICATIONS

VV-NC41336B-F3WLIRT1

Camera	Image Sensor	1/2.7" progressive scan CMOS sensor
	Signal System	PAL/NTSC
	Effective Pixels	3200 (H) × 1800 (V)
	Minimum Illumination	Color : 0.007 lux @F1.6, AGC ON; 0 lux with illuminator on
	Electronic Shutter Speed	1 / 2s ~ 1 / 100000s
	Gain Control	Auto
	Signal to Noise	> 50 dB
	Iris	Fixed
Lens	Lens Type	3.6mm@F1.6 fixed lens (2.8mm optional)
	Lens Mount	M12
	Focus	Fixed
	FOV	Horizontal FoV:91.5°;Vertical FoV:49.5°; Diagonal FoV:107°
Day/Night Functionality	Night Vision	True day & night with ICR
	IR Cut	High performance mechanical IR cut filter with auto switch
	IR Source	Inbuilt smart IR LEDs with intensity control
	Supplement Light Range	IR range: 20 ~ 30 m; white light range:10 ~ 20 m
Compression	Video Compression	H.265+ / H.265 / H.264 + / H.264 / MJPEG
	H.265 Codec Profile	Main Profile@Level4.1 High Tier
	Audio Compression	G711A/U
	Video Bit Rate	64Kbps ~ 8Mbps
Resolution and Frame Rate	Max. Resolution	6MP(3200×1800), 4MP (2688×1520), 1080P (1920×1080), 720P (1280 × 720), D1, VGA(640×480), 480× 240, CIF
	Main Stream	50Hz: 6MP(1~20fps)/4MP/1080P(1~25fps) 60Hz: 6MP(1~20fps)/4MP/1080P(1~30fps);
	Sub Stream	50Hz: 720P/D1/VGA/ CIF/480× 240(1~25fps) 60Hz: 720P/D1/VGA/ CIF/480× 240(1~30fps);
Operational Features	Wide Dynamic Range (WDR)	Digital WDR
	BLC	Supported
	ROI	Each ROI to be configured separately
	HLC	Supported
	DNR	Inbuilt 3D DNR (Digital Noise Reduction) circuit
	Codec Streaming Capability	Dual streaming
	Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
	Motion Detection	Support smart motion detection; filtering motion alarm triggered by other target types except humans
	General Function	Watermark, video mask, heartbeat
	Security	Video encryption, firmware encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP
Network & Remote Monitoring	Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, 802.1x, HTTP
	System Compatibility	ONVIF
	CMS	Full function CMS (Central monitoring software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth Control	VBR (Automatic) and CBR (Manual) supported
	Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
	Web Browser	IE 11 (plug-in required)/Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+
	Storage	Network remote storage

TECHNICAL SPECIFICATIONS


VV-NC41336B-F3WLIRT1

Analytics Feature	Smart Features	(Human) region intrusion detection, (human)line crossing detection			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8mm	60m(196ft)	24m(78ft)	12m(39ft)	6m(20ft)
	3.6mm	71m(233ft)	28m(93ft)	14m(47ft)	7m(23ft)
Interface	Ethernet	1 RJ45 Ethernet port			
	Audio	1CH built-in MIC			
Electrical	Power Requirement	DC12V/PoE (IEEE802.3af)			
	Power Consumption	Max. <6W			
Environmental	Enclosure	IP67 weather proof enclosure			
	Operating Temperature	-30°C to + 65°C			
	Operating Humidity	95% or less (non-condensing)			
Mechanical	Installation	Ceiling mounting; Wall mounting			
	Dimensions	167.6 × 75 × 74.6mm			
	Weight	Approx. 0.382KG			
Certifications	Certifications	CE, FCC, RoHS			

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary due to customized solutions & products being offered as per customer requirements.

DIMENSIONS

Unit: mm



VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

