

FULL HIGH DEFINITION 5MP IP PTZ CAMERA

VV-NC8335P-Z10IR2B1
IR Night Vision High Speed PTZ Dome Camera



FEATURES

Full High Definition 5MP (2592 x 1944) resolution

1/3" Progressive Scan Sensor

10x Optical zoom

360° endless panning

Inbuilt IR LEDs for 50 mtrs IR range

Supports presets/ pattern/patrol/pan scan

Inbuilt DWDR, 3D DNR & BLC



1/3"
Progressive
Scan Sensor

**FULL
HD**
1080P



Backlight
Compensation



Dual
Stream



360°
Endless Panning

TECHNICAL SPECIFICATIONS

VV-NC8335P-Z10IR2B1

Camera	Image sensor	1/3" Progressive Scan Sensor
	Signal System	PAL/NTSC
	Effective Pixels	2592 (H) x 1944 (V)
	Minimum Illumination	Color: 0.001Lux@(F1.4, AGC ON) B/W: 0.0015Lux@(F1.4, AGC ON); 0 Lux with IR
	Electronic Shutter Speed	1/1~ 1/10,000s
	Signal to Noise	> 52 dB
	Gain Control	Auto / Manual
	White Balance	Auto/Manual/ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
	Iris	Auto Iris
Lens	Lens Type	5.1- 51mm Optical Lens
	Angle of View	47-5.3 degree (Wide-Tele)
	Focus	Auto Focus
	Zoom	10x Optical Zoom
	Zoom Speed	Approx.1s (Optical Wide-Tele)
	Aperture Range	F1.4 ~ F3.5
Compression	Video compression	H.265/ H.264 / MJPEG
	H.264 codec profile	Main profile
	Video Bit Rate	32 Kbps ~ 16 Mbps
Resolution and Frame Rate	Max. Resolution	2592x1944
	Main Stream	50Hz: 15 fps(2592x1944,2592x1520),25 fps(1920x1080,1280x720) 60Hz: 15 fps(2592x1944,2592x1520),30 fps(1920x1080,1280x720)
Day/Night Functionality	Day & Night	True Day & Night with ICR
	IR Cut	High performance Mechanical IR Cut Filter with auto switch
	IR Source	Inbuilt High performance IR LEDs
	IR Range	Up to 50 Mtrs
	IR Irradiation Angle	Automatically adjusted, depending on the zoom ratio
	IR Life	40000 operation hours
Pan-Tilt	Pan Angle	360° endless pan rotation
	Tilt Angle	0° to 93° (Auto Flip)
	Pan Speed	0.01° ~ 200°/s
	Tilt Speed	0.01° ~ 100°/s
	Presets	220
	Preset Accuracy	± 0.1°
	Patrol	3 patrols, up to 16 presets per patrol
	Pattern	Supported
	Power-off Memory	Supported
	PTZ position display	Supported
	Operational Features	OSD Menu
Camera ID		On/Off
Privacy Masking		Yes multiple zone supported
Digital Zoom		16x Digital Zoom
Motion Detection		Supported
Backlight Compensation		Supported
Video Adjustment		Supported
WDR		D-WDR
Protocols		PELCO-P, PELCO-D, Multi protocol support
Baud Rate		2400/4800/9600bps
DNR	Inbuilt 2D/ 3D DNR (Digital Noise Reduction) circuit	

TECHNICAL SPECIFICATIONS

VV-NC8335P-Z10IR2B1

	Codec streaming capability	Dual streaming
	Image settings	Rotate mode, Saturation, brightness, contrast, sharpness adjustable through client software or web browser
	Security	User authentication, watermark, IP address filtering, anonymous access, reset
Network & Remote Monitoring	Protocols	IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPnP,SNMP,DNS,DDNS,NTP,RTSP,RTP,TCP/IP ,DHCP, PPPoE
	System compatibility	ONVIF
	CMS	Full function CMS (Central monitoring software)
	User Access	32 users online with professional authority management
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	VBR (Automatic) and CBR (Manual) supported
	Onboard storage	Built-in Micro SD / SDHC / SDXC card slot, up to 128 GB (Optional)
Interface	Ethernet	1 RJ45 10/100 Ethernet port
	Power Input	Standard DC Jack / 2 pin wire terminal
	Audio Input/Output	1/1(Optional)
	Alarm Input/Output	1/1(Optional)
Electrical	Power Requirement (± 10%)	12VDC,4A/ 24V AC,3A
	Power Consumption	MAX. 22W
Environmental	Enclosure	IP66 Weatherproof Outdoor Enclosure
	Mounting bracket	External Mounting bracket included
	Operating Temperature	-40°C to +65°C
	Operating Humidity	95% or less (non-condensing)
Mechanical	Color	White
Certification	Certifications	CE, FCC, RoHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

