

FULL HIGH DEFINITION H.265 2MP IP DOME CAMERA

VV-NC91152D-AZIR2T1 IR NIGHT VISION MOTORIZED CAMERA



FEATURES

- Full High Definition 2MP (1920 x 1080) resolution
- H.265 video compression technology with real time encoding
- Inbuilt High intensity Smart IR LEDs with intensity control
- Inbuilt True 120db WDR, 3D DNR,HLC, Defog & BLC functions
- Supports triple streams
- One way audio Supported
- Inbuilt SD card Slot up to 128GB Supported
- IP67 Weather proof outdoor enclosure



VV-NC91152D-AZIR2T1

| | | |
|-----------------------------|----------------------------|--|
| Camera | Image sensor | 1/2.8" Progressive Scan CMOS Sensor |
| | Signal System | PAL/NTSC |
| | Effective Pixels | 1920 (H) x 1080 (V) |
| | Minimum Illumination | Color : 0.005Lux @ F1.6, B&W: 0 Lux at IR |
| | Electronic Shutter Speed | 1/25s ~ 1/100,000s |
| | Gain Control | Auto |
| | White Balance | Auto |
| | Signal to Noise | > 52 dB |
| | Iris | Auto Iris |
| Lens | Lens Type | 2.8~12mm@F1.4, motorized zoom lens |
| | Focus | Auto |
| | Zoom | Motorized Optical Zoom Adjustment |
| Day/Night Functionality | Day & Night | True Day & Night with ICR |
| | IR Cut | High performance Mechanical IR Cut Filter with auto switch |
| | IR Source | Inbuilt high intensity Smart IR LEDs with intensity control |
| | IR Range | Up to 50 Mtr. |
| | IR Life | 40000 Operation Hours |
| Compression | Video compression | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| | H.264 codec profile | Main profile |
| | Video Bit Rate | 128 Kbps ~ 6 Mbps |
| | Audio compression | G.711A / G.711U |
| | Audio Bit Rate | 64 Kbps |
| Resolution and Frame Rate | Max. Resolution | 1920 x 1080 |
| | Main Stream | 50Hz: 25fps (1920 x 1080), 25fps (1280 x 720), 25fps (704 x 480) 60Hz: 30fps (1920 x 1080), 30fps (1280 x 720), 30fps (704 x 480) |
| | Sub/ Third Stream | 60Hz: 25fps (1280 x 720), 25fps (704 x 480), 25fps (352 x 240) 60Hz: 30fps (1280 x 720), 30fps (704 x 480), 30fps (352 x 240) |
| Operational Features | Wide Dynamic Range (WDR) | 120 dB |
| | BLC & HLC | Yes, zone configurable |
| | DNR | Inbuilt 3D DNR (Digital Noise Reduction) circuit |
| | ROI | Supported |
| | Codec streaming capability | Triple streaming |
| | Image settings | Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR Defog, etc. adjustable through client software or web browser |
| | Privacy Masking | Supported |
| | Security | User Authentication, Watermark, Heartbeat, IP address filtering, IP address filtering, video mask, image distortion correction |
| | Onboard Storage | Built-in Micro SD / SDHC / SDXC card slot, up to 128 GB |
| | Alarm trigger | Motion detection, Tampering alarm, Smart Analytics, SD card error, SD card full, IP address conflict, Network disconnection |
| Network & Remote Monitoring | Protocols | UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, |
| | System compatibility | ONVIF |
| | CMS | Full function CMS (Central monitoring software) |
| | Mobile Client Application | Supports android and iOS APP for Smart phone and tablets |
| | Bandwidth control | VBR (Automatic) and CBR (Manual) supported |
| Interface | Ethernet | 1 RJ45 10/100 Ethernet port |
| | Power Input | Standard DC Jack |
| | Audio Input | 1CH audio input; Built-in MIC x 1 |

TECHNICAL SPECIFICATIONS


WV-NC91152D-AZIR2T1

| | | |
|----------------|-----------------------|---|
| Features | Smart Analytics | Line crossing, region entrance/exiting/intrusion (human/motor vehicle/Perimeter Protection non-motor vehicle classification), Target Counting, Scene change, video blur and video color cast detection, Face detection and face capture |
| Electrical | Power Requirement | 12 VDC \pm 10% , PoE (802.3af) |
| | Power Consumption | Max. 7W |
| Environmental | Enclosure | IP67 Weatherproof outdoor enclosure |
| | Mounting bracket | Integrated mounting bracket with cable management |
| | Operating Temperature | -30°C to + 60°C |
| | Operating Humidity | 95% or less (non-condensing) |
| Mechanical | Color | White |
| | Dimensions | 94.6 x 82.8 mm |
| | Weight | 460g |
| Certifications | Certifications | CE, FCC, RoHS |

Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

DIMENSIONS

Unit: mm



VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

