

FULL HIGH DEFINITION 2MP IP MINI DOME CAMERA

VV-NC9412D-AF3IRT1
IR NIGHT VISION FIXED CAMERA



FEATURES

Full HD 2MP (1920 x 1080) resolution

1/2.8" Progressive Scan CMOS Sensor

Inbuilt smart IR LEDs with intensity control

High performance IR Cut mechanical filter for
True Day & Night vision

Inbuilt 120 dB WDR, 3D DNR, HLC, BLC & ROI functions

Support triple streams

Support intelligent analytics

IP67 Weather proof outdoor enclosure



1/2.8"
Progressive
Scan CMOS Sensor



Backlight
Compensation



Smart IR



POE



IP67
Weather Proof

TECHNICAL SPECIFICATIONS

VV-NC9412D-AF3IRT1

| | | |
|-----------------------------|--|--|
| Camera | Image Sensor | 1/2.8" Progressive Scan CMOS Sensor |
| | Signal System | PAL/NTSC |
| | Effective Pixels | 1920 (H) x 1080 (V) |
| | Minimum Illumination | Color : 0.005 lux @F1.6, AGC ON; 0 lux with IR |
| | Electronic Shutter Speed | 1/3s ~ 1 / 100000s |
| | Gain Control | Auto |
| | Signal to Noise | > 50 dB |
| | Iris | Fixed |
| Lens | Lens Type | 3.6mm@ F1.6, (2.8mm optional) |
| | Lens Mount | M12 |
| | FOV | Horizontal FoV: 138.5°; vertical FoV: 80.1°; diagonal FoV: 156.5° |
| | Focus | Fixed |
| Day/Night Functionality | Day & Night | True Day & Night with ICR |
| | IR Cut | High performance Mechanical IR Cut Filter with auto switch |
| | IR Source | Inbuilt Smart IR LEDs with intensity control |
| | IR Range | 10~20 Mtr. |
| Compression | Video Compression | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| | H.264 codec profile | Baseline Profile/Main Profile/High Profile |
| | Video Bit Rate | 64 Kbps ~ 6 Mbps |
| | Audio Compression | G711A / U |
| Resolution and Frame Rate | Max. Resolution | 1080P(1920x1080), 720P(1280x720), D1, VGA(640x480), 640x360, 480x240, CIF |
| | Main Stream | 1080P/720P(60Hz: 1 ~ 30fps; 50Hz: 1 ~ 25fps) |
| | Sub Stream | 720P/D1/VGA/640x360/480x240/CIF(60Hz: 1 ~ 30fps; 50Hz: 1 ~ 25fps) |
| | Third Stream | D1/CIF/480x240(60Hz: 1 ~ 30fps; 50Hz: 1 ~ 25fps) |
| Operational Features | Wide Dynamic Range (WDR) | 120dB WDR |
| | BLC | Supported |
| | ROI | Each ROI to be configured separately |
| | Defog | Supported |
| | EIS | Supported |
| | HLC | Supported |
| | DNR | Inbuilt 3D DNR (Digital Noise Reduction) circuit |
| | Codec Streaming Capability | Triple streaming |
| | Image Settings | ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, Image Flip, Image Mirror, etc. adjustable through client software or web browser |
| | Alarm Trigger | Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, cable disconnection |
| Network & Remote Monitoring | General Function | Watermark, video mask, heartbeat, image distortion correction, corridor pattern, ANR |
| | Security | Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP |
| | Protocols | UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTMP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, HTTP POST, 802.1x, UPnP, HTTPS, P2P, QoS |
| | System Compatibility | ONVIF |
| | CMS | Full function CMS (Central monitoring software) |
| | Mobile Client Application | Supports android and iOS APP for Smart phone and tablets |
| | Bandwidth Control | VBR (Automatic) and CBR (Manual) supported |
| | Web Browser | IE11(plug-in required)/Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+ |
| Online Connection | Support simultaneous monitoring for up to 8 users; | |
| | Support multi-stream real time transmission | |
| Storage | Built-in micro SD card slot, up to 256GB | |

TECHNICAL SPECIFICATIONS



VV-NC9412D-AF3IRT1

| | | |
|----------------|-----------------------|--|
| Interface | Ethernet | RJ 45 10M/100M self-adaptive Ethernet port |
| | Power Input | Standard DC Jack |
| | Audio Input/Output | 1CH audio input; 1CH audio output; 2CH built-in MIC |
| | Alarm Input/Output | 1CH alarm input; 1CH alarm output |
| Smart Features | Smart Analytics | Line crossing, region intrusion/entrance/exiting, loitering detection, illegal parking detection, abandoned/ missing object detection |
| | Statistics | Target counting by line/area, heat map |
| | Exception Detection | Scene change, video blur and video cast detection, audio exception |
| | Face Detection | Face detection and face capture |
| | Video Metadata | Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 5 motor vehicle features and 1 non-motor vehicle feature |
| Electrical | Power Requirement | DC12V/PoE (IEEE802.3af) |
| | Power Consumption | Max. <3.5W |
| Environmental | Enclosure | IP67 Weather proof outdoor enclosure |
| | Operating Temperature | -30°C to + 60°C |
| | Storage Temperature | -30°C to + 65°C |
| | Operating Humidity | 95% or less (non-condensing) |
| Mechanical | Color | White |
| | Dimensions | Ø 110 x 62 |
| | Weight | Approx. 0.41KG |
| Certifications | Certifications | CE, FCC, RoHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

DIMENSIONS

Unit: mm



VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton
West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com
www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

