

# HIGH PERFORMANCE NETWORK VIDEO RECORDER

## VV-NV2004-1SL3 4 CHANNEL NVR



### FEATURES

ONVIF Supported

Up to 2 Megapixels Resolution Display and Recording

HDMI and VGA output at up to 1920x1080P resolution

Full function CMS (Central monitoring software) supported

Two way audio supported

10/100Mbps Self-adaptive Ethernet Interface

Dual streaming technology to encode recording stream and network stream separately

Supports remote monitoring on Mobile Client (Android, IOS) and IE



**Motion  
Detection**



**E-mail  
Alert**



**Mobile  
Monitoring**

## TECHNICAL SPECIFICATIONS

# VV-NV2004-1SL3

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	User interface	Support 16-bit true color graphical menu interface and mouse operation
Interface	IP Video Input	4-ch
	Two way Audio Input	1-ch, RCA (Linear, 1k $\Omega$ )
	VGA Video Output	1920x1080P/60Hz, 1280x1024/60Hz, 1280x720/60Hz
	HDMI Video Output	1920x1080P/60Hz, 1280x1024/60Hz, 1280x720/60Hz
	Audio Output	1-ch, RCA (Linear, 1k $\Omega$ )
	Network	10/100Mbps Self-adaptive Ethernet Interface
	USB	2 x 2.0 USB interface (for backup, firmware upgrade and mouse interface)
Resolution & Frame Rate	Recording Resolution	1080P /960P /720P /4CIF
	Frame Rate	Main stream: 25 fps (P) / 30 fps (N); Sub stream: 25 fps (P) / 30 fps (N)
	Playback Resolution	1080P/720P
	Max playback capability	Max 4 ch playback
Network & Remote Monitoring	DDNS	Supported; Dynamic and Static IP support
	CMS	Full function CMS (Central Monitoring Software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	VBR/ CBR (Manual) supported
Features	Security	Password protection, user management
	Playback Function	Play/Pause/Fast forward / backward/Digital zoom
	Search Mode	Time/Date, Alarm, Motion Detection & Exact Search (accurate to second)
	Alarm Notifications	FTP, Email notification supported
Recording & Storage	Recording Mode	Manual/Motion Detection/Continuous
	Storage	1 SATA port up to 6TB
	Overwrite Mode	Supported
General	Power Supply	DC 12V
	Power Consumption	<12W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	95% or less (non condensing)
	Chassis	Standalone 1U chassis
	Dimensions	260 x 215 x 43 mm
	Weight	2Kg
Certification	Certification	CE, FCC, RoHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Product image, weights and measurements are approximate and may vary.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

