

# HIGH PERFORMANCE

## H.265 NETWORK VIDEO RECORDER

# VV-NV3508-FP2ST1

## 8 CHANNEL POE NVR



### FEATURES

ONVIF Supported

Up to 5 Megapixels Resolution and Recording

H.265 video compression technology with real time encoding

Full function CMS (Central monitoring software) supported

Dual streaming technology to encode recording stream and network stream separately

Supports remote monitoring on Mobile Client (Android, IOS) and IE



**POE**



**Motion  
Detection**



**E-mail  
Alert**



**Mobile  
Monitoring**

## TECHNICAL SPECIFICATIONS



### VV-NV3508-FP2ST1

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	User interface	Support 16-bit true color graphical menu interface and mouse operation
Interface	Total Bandwidth	50 Mbps
	IP Video Input	8-ch
	HDMI Video Output	1-ch, Resolution: 1920x1080 / 1280 X 1024
	Network	1 x (10/100) ethernet port (RJ45)
	USB	USB 2.0 x 2 (one for mouse, another for USB backup device)
Resolution & Frame Rate	Recording Resolution	5MP/ 4MP / 3MP / 1080P / 720P / 4CIF
	Frame Rate	Main stream: 25 fps (P) / 30 fps (N) Sub stream: 25 fps (P) / 30 fps (N)
	Playback Resolution	5MP/ 4MP / 3MP / 1080P / 720P / 4CIF
	Max playback capability	Max 8 ch playback
Network & Remote Monitoring	DDNS	Supported; Dynamic and Static IP support
	CMS	Full function CMS (Central Monitoring Software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
	Bandwidth control	CBR/VBR supported
Features	Security	Password protection, User management
	Playback Function	Play/ Pause/ Fast forward / Backward/Digital zoom
	Search Mode	Time/Date, Alarm, Motion Detection & Exact Search
	Alarm Notifications	FTP, Email notification supported
Recording & Storage	Recording Mode	Manual/ Alarm/ Motion Detection/ Continuous
	Storage	2 SATA port up to 6TB each
	Overwrite Mode	Supported
General	Power Supply	DC48V
	Power Consumption	<5W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	95% or less (non condensing)
	Dimensions	380 x 268 x 52 mm
	Weight	≤4Kg ( without hard disk)
Certifications	Certifications	CE,FCC,RoHS

\*Actual product and specifications may differ from the images appearing in the brochure and are subject to change without notice due to ongoing product development.

## DIMENSIONS

Unit: mm



## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO 14001: 2004 CERTIFIED COMPANY)

