

HIGH PERFORMANCE

H.265 NETWORK VIDEO RECORDER

VV-NV3564-8ST1

64 CHANNEL NVR



FEATURES

ONVIF Supported

Up to 8 Megapixels Resolution Display and Recording

H.265 video compression technology with real time encoding

Full function CMS (Central monitoring software) supported

Two way audio supported

2x Gigabit (10/100/1000) network port

Dual streaming technology to encode recording stream and network stream separately

Supports remote monitoring on Mobile Client (Android, IOS) and IE



TCP/IP



Motion
Detection



E-mail
Alert



Mobile
Monitoring

TECHNICAL SPECIFICATIONS

VV-NV3564-8ST1

System	Operating System	Embedded Linux Operating System
	Multiplex Operations	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
	User interface	Support 16-bit true color graphical menu interface and mouse operation
Bandwidth	Incoming/Outgoing	320Mbps / 320Mbps
Interface	IP Video Input	64-ch
	Two way Audio Input	1-ch, RCA
	VGA Video Output	1-ch, Resolution: 1920x1080P/1280x1024
	HDMI Output 1	4K x 2K / 1920 x 1080 / 1280 x 1024
	HDMI Output 2	1920 x 1080 / 1280 x 1024
	Audio Output	1-ch, RCA
	Network	2 x Gigabit (10/100/1000) ethernet port (RJ45)
	USB	USB 3.0 x 1, x USB 2.0 x 2
	Alarm Input	8 CH
	Alarm Output	4 CH
Resolution & Frame Rate	RS-485 Port	Rs485 x 1
	Recording Resolution	8MP / 5MP/ 4Mp / 3MP / 1080P / 720P / 4CIF
	Frame Rate	Main stream: 25 fps (P) / 30 fps (N); Sub stream: 25 fps (P) / 30 fps (N)
	Playback Resolution	8MP / 5MP/ 4Mp / 3MP / 1080P / 720P / 4CIF
Network & Remote Monitoring	Max playback capability	Max 16 ch playback
	DDNS	Supported; Dynamic and Static IP support
	CMS	Full function CMS (Central Monitoring Software)
	Mobile Client Application	Supports android and iOS APP for Smart phone and tablets
Features	Bandwidth control	CBR (Manual) supported
	Security	Password protection, user management
	Playback Function	Play/Pause/Fast forward / backward/Digital zoom
	Search Mode	Time/Date, Alarm, Motion Detection & Exact Search (accurate to second)
Recording & Storage	Alarm Notifications	FTP, Email notification supported
	Recording Mode	Manual/Alarm/Motion Detection/Continuous
	Storage	8 SATA port up to 6TB each
	e-SATA	e-SATA x 2
General	Overwrite Mode	Supported
	Power Supply	AC 220V
	Power Consumption	<15W (Hard disk not included)
	Operating temperature	-10°C to + 55°C
	Working Humidity	95% or less (non condensing)
	Chassis	Standalone 1U chassis
	Dimensions	430 x 453 x 89 (W x D x H)mm
Certifications	Weight	≤ 4 Kg (without hard disk)
	Certifications	CE, FCC, RoHS

*Actual product and specifications may differ from the images appearing in the brochure and are subject to change without notice due to ongoing product development.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001: 2004 CERTIFIED COMPANY)

