

# RFID BASED ACCESS CONTROL SYSTEM

## VV-RF101-26BE2 ENTRY/EXIT READERS



### FEATURES

Wiegand-based Entry/Exit Readers

Operating frequency of 125 kHz

Read range of 3-5cm,

Wiegand transmit distance: 100Mtr

Multi-cards simultaneous read ability

Lightning proof protection



Multicolor LED  
Indication



EM Card



Buzzer  
Sound

## TECHNICAL SPECIFICATIONS

### W-RF101-26BE2

Parameter	Specifications
Working Voltage	DC 9 ~16V
Working current	<=100mA
Communication Distance	<=100 Mtr
Reading Range	3 to 5cm
Dimension	42X 80 X 12.5(mm)
Output Format	Wiegand 26/44
Working Temperature	-10~+70 °C
Working Humidity	10% to 95% R.H
Card Type	EM-ID/Mifare
Certifications	CE, FCC, ROHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

