

RFID BASED ACCESS CONTROL SYSTEM

VV-RF105-26BE2 RFID ENTRY/EXIT READERS



FEATURES

Wiegand-based Entry/Exit Readers

Operating frequency of 125 kHz

Read range of 3-5cm,

Wiegand transmit distance: 200Mtr

Multi-cards simultaneous read ability

Lightning proof protection

Premium ABS enclosure with blue LED indication



Multicolor LED
Indication



EM Card



Buzzer
Sound

TECHNICAL SPECIFICATIONS

WV-RF105-26BE2

Parameter	Specifications
Working Voltage	DC 9 ~16V
Working current	<=100mA
Communication Distance	<=100 Mtr
Reading Range	3 to 5cm
Dimension	100 X 46 X 20(mm)
Output Format	Wiegand 26/44
Working Temperature	-10~+70 °C
Working Humidity	10% to 95% R.H
Card Type	EM-ID/Mifare
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

