

RFID BASED ACCESS CONTROL SYSTEM

VV-RF105-26BE2 RFID ENTRY/EXIT READERS



FEATURES

- Compact and durable design
- Communication distance up to 100 m
- Easy integration with third-party access control systems
- Premium ABS enclosure with LED indicator
- IP65 weatherproof housing for outdoor use



Multicolor LED
Indication



EM Card



Buzzer
Sound

TECHNICAL SPECIFICATIONS

VV-RF105-26BE2

Parameter	Specifications
Supported Card Types	Standard EM 125 kHz , optional MIFARE 13.56 MHZ
Reading Distance	3 – 5 cm
Communication Distance	Up to 100 m
Standard Interface	Wiegand
Output Format	Wiegand 26 / 34
Input Voltage	DC 9V - 16V
Working Temperature	-20~+70 °C
IP Rating	IP65
Dimensions	100 x 46 x 20 mm
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

READER INTERFACE:

Terminal	Color
DC 9V-16V	Red
Ground	Black
Data 0	Green
Data 1	White
Beep	Yellow
Grey	GND (for Wiegand 34 selection)



VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

