

# RFID BASED ACCESS CONTROL SYSTEM

## VV-RF200U-EME2 USB BASED RFID ENROLLMENT READER



### FEATURES

- Desktop based USB reader for RFID card enrollment
- Supports 125 kHz cards, optional 13.56 MHz MIFARE
- Read range of 2–3 cm
- Plug-and-play USB interface for easy integration with software
- Tabletop design for convenient operation
- Compact and lightweight design



Multicolor LED  
Indication



EM Card



Buzzer  
Sound

## TECHNICAL SPECIFICATIONS:

### WV-RF200U-EME2

Parameter	Specifications
Working Voltage	DC 5V (USB Powered)
Working Current	≤ 100 mA
Reading Range	3 - 5 cm
Output Interface	USB
Supported Cards	Standard EM 125 kHz , optional MIFARE 13.56 MHz
Working Temperature	.-10°C to +70°C
Working Humidity	10% - 95% RH
Color	Black
Dimensions	110 x 80 x 25 mm
Certifications	CE, FCC, ROHS

\*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

## VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph:+44-1902-793383, Email: sales@vantagesecurity.com

[www.vantagesecurity.com](http://www.vantagesecurity.com)

(AN ISO 9001 : 2008, ISO 14001 : 2004 CERTIFIED COMPANY)

