

SECURITY ALARM SYSTEMS ACCESSORIES

VV-SA655AX-GSK2 DIGITAL DISPLAY WIRELESS GAS DETECTOR



 **Safe Homes.
Safe Communities.**

FEATURES

- Human voice prompt
- High reliable catalytic combustion method
- Gas concentration displaying (PPM)
- Power supply from AC 100V-240V with build-in battery
- Intelligent micro processor control
- Auto detect sensor failure
- Auto send notification to host when alarm
- One relay output when alarm



Wireless



LED



Digital
Display



Built-In
Battery

TECHNICAL SPECIFICATIONS

WV-SA655AX-GSK2

| Parameter | Specifications |
|----------------------------|------------------------------------|
| Power Supply | 100V~240V AC 50-60Hz |
| Battery Voltage | 9V rechargeable battery (optional) |
| Working Temperature | 0-50°C |
| Environment Humidity | 10% - 95% |
| Alarm Density | 2500PPM (\pm 1500PPM) |
| Alarm Time | Keep alarming after over 2500PPM |
| Wireless Working Frequency | 433MHz |
| Wireless Working Distance | \leq 25m |
| Size | 120x80x35mm |
| Certifications | CE, FCC, ROHS |

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton
West Midlands, WV6 0JZ United Kingdom
Ph: +44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

