

SECURITY ALARM SYSTEMS ACCESSORIES

VV-SA620AX-MCK2

WIRELESS DOOR/ WINDOW MAGNETIC CONTACT SENSOR



 **Safe Homes.
Safe Communities.**

FEATURES

Built-in antenna

Tamper protection

Power Supply DC 12V (23A Battery x 1 pc)

Operating frequency 433MHz

Transmitting distance: $\leq 25\text{m}$



Wireless



LED



Temper

TECHNICAL SPECIFICATIONS

VV-SA620AX-MCK2

Parameter	Specifications
Power Supply	DC 12V (23A Battery x 1 pc)
Standby Current	$\leq 25\mu\text{A}$
Alarm Current	$\leq 20\text{mA}$
Transmitting Distance	$\leq 25\text{m}$
Radio Frequency	433MHz
Housing Material	ABS plastic
Working Temperature	$-10^{\circ}\text{C}\sim 55^{\circ}\text{C}$
Working Humidity	$\leq 80\%$ (non-condensing)
Dimensions Transmitter (L x W x H)	77*23*15 mm
Dimensions Magnet (L x W x H)	64*13 *13 mm
Certifications	CE, FCC, ROHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

DIMENSIONS

Unit: mm



VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED.

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902-793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO 14001:2004 CERTIFIED COMPANY)

